

**Trenta Collection**

**DESIGN**

Product Type:	Glue Down LVT
Gauge:	.12" (3mm)
Wear Layer:	30 mil (0.7mm)
Finish:	Commercial Grade Urethane
Size:	12" W x 24" L
Square Feet Per Carton:	36 sf/ctn (3.34 m <sup>2</sup> /ctn)
Pieces Per Carton:	18 pieces/ctn
Installation Method:	Glue Down
Recommended Adhesive:	M95.0 Resilient Floor Adhesive, MS160 Spray Adhesive or M700 Pressure Sensitive Adhesive

**PERFORMANCE**

Construction:	Heavy Commercial Grade Enhanced Resilient Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size and Tolerance:	ASTM F2055 - Passes - $\pm 0.016$ in. per linear foot
Thickness:	ASTM F386 - Passes - Nominal $\pm 0.005$ in.
Flexibility:	ASTM F137 - Passes - 1.0 inch mandrel, no cracks or breaks
Dimensional Stability:	ASTM F2199 - Passes - $\leq 0.020$ in. per linear foot
Static Load:	ASTM F970 - Passes, modified - 2500 psi
Residual Indentation:	ASTM F1914 - Passes - Residual $\leq 8\%$
Slip Resistant:	ASTM D2047 - Passes - $> 0.6$ Dry
Resistance To Chemicals:	ASTM F925 - Passes - No Change
Resistance To Light:	ASTM F1515 - Passes - $\Delta E \leq 8$
Resistance To Heat:	ASTM F1514 - Passes - $\Delta E \leq 8$
Critical Radiant Flux:	ASTM E648 - Passes - Class 1, $> 0.45$ watts/cm <sup>2</sup>
Smoke Density:	ASTM E662 - Passes - $\leq 450$
Impact Insulation Class:	ASTM E989 / E492 - 59 IIC

**SUSTAINABILITY**

Certification:	FloorScore® certified
----------------	-----------------------

**SERVICE**

Warranties:	Limited 20 Year Commercial
-------------	----------------------------



138  
Sheer Linen



358  
Hearth



837  
Oyster



945  
Silver Screen



958  
Windsor