



Product Specifications

Construction	Tip-Sheared Scroll
Backing	Woven Polypropylene (standard backing)
Dye Method	Solution Dyed
Nylon Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	24 oz./sy (814 grams/m2)
Pile Density	5838 oz./y3 (216.48 kg/m3)
Pattern Repeat	24.00" (w) x 48.00" (l) approx. (60.96cm x 121.92cm)
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	11.66 stitches/in (4.59 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Encore SD Ultima Fiber
Optional Warranties	TitanBac Plus Endure Plus


Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional


Environmental Specifications & Tests

NSF 140:	N/A Certified
Total Recycled Content	25%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways




STC10 Tatami




STC32 Tinsel




STC36 Spa Spun




STC38 Reed




STC45 Shadow




STC48 Denim




STC52 Grey Twill




STC58 Rattan




STC72 Knitting Nee...



STC77 Tapestry Ta...



STC78 Suitable Br...



STC86 Shuttle Bro...