

## ARIZONA TILE

## SAVANNAH SERIES



Savannah Milk



Savannah Coffee



Savannah Cream



Savannah Dust



Savannah Honey



Savannah Milk



Savannah Sepia



## MADE IN ITALY

## PRODUCT TYPE

Rectified Color Body Porcelain  
Digital Print Technology

## COLORS

Savannah Coffee  
Savannah Cream  
Savannah Dust  
Savannah Honey  
Savannah Milk  
Savannah Sepia

## STOCKED SIZES

6" × 24" × 10mm  
4" × 40" × 10mm  
8" × 40" × 10mm

## RECOMMENDED USES

Commercial  
Residential  
Interior Floor  
\*Exterior Floor  
Countertops  
Interior Wall  
Exterior Cladding  
Fireplaces  
Showers  
Steam Showers  
Pool & Spa (waterline)

**C.O.F. DRY: 0.76**

**C.O.F. WET: 0.68**

**DYNAMIC C.O.F. WET: 0.56**

**P.E.I. RATING: 4**

**FROSTPROOF: Yes**

\*DCOF Rating is a measurement of a tiles frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

The Savannah Series is a rectified color body porcelain. It is the synthesis of digital technology applied to aesthetic research. Giving the appearance of visual perfection and the elegance of clean, welcoming ambiances, the Savannah Series reflects the soul of wood with its timeless beauty and silent perfect lines. Because this material is a porcelain product, minimal maintenance is required. Savannah Series is available in three sizes and six colors. Numerous patterns can be created with the available sizes. Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications. For proper bonding, medium bed mortar should be used when installing tiles with a dimensional length greater than 15", and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
6" × 24" × 10mm	0.9684	12	11.6208	40	464.832
4" × 40" × 10mm	1.076	10	10.76	36	387.36
8" × 40" × 10mm	2.152	5	10.76	36	387.36

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.

[www.arizonatile.com](http://www.arizonatile.com)