ARIZONA TILE

THEMAR SERIES



Themar Statuario



Themar Bianco Lasa



Themar Bianco Lasa Hex



Themar Crema Marfil



Themar Crema Marfil Hex



Themar Grigio Savoia



Themar Grigio Savoia Hex



Themar Statuario V



Themar Statuario V Hex



Themar Venato Gold



Themar Venato Gold Hex

MADE IN ITALY

PRODUCT TYPE

Rectified Glazed Porcelain Digital Print Technology

COLORS

Themar Bianco Lasa Themar Crema Marfil Themar Grigio Savoia Themar Statuario V Themar Venato Gold

FINISHES

Matte Polished

STOCKED SIZES

3" × 12" × 10mm 12" × 24" × 10mm 24" × 24" × 10mm 2" × 2" × 10mm Mosaic Hex 2-3/8" × 2-3/8" × 10mm

RECOMMENDED USES

Commercial Residential Interior Floor **Exterior Floor (matte finish only)

Countertops
Interior Wall
Exterior Cladding
Fireplaces
Showers
*Shower Floors
Steam Showers
Pool & Spa (waterline)

*2" × 2" Mosaic and Hex 2-3/8 only

STOCKED TRIM

 $1/2" \times 11-5/8"$ pencil bullnose $3" \times 12"$ SBN

P.E.I. RATING: 5 (matte)

4 (polished)

FROSTPROOF: Yes

D.C.O.F. WET: 0.42 (matte)

**DCOF Rating is a measurement of a tiles frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

The Themar Series is a rectified glazed porcelain. Digital print technology creates some of the same characteristics as some of the most sought-after natural stones, including marble. Because this material is a porcelain product, maintenance risks involved with actual stone are eliminated. There will be noticeable variations in color and movement between pieces. Therefore, it is important and recommended that a range of this product be viewed before finalizing a purchase. Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. This series is suitable for residential and commercial applications. For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15" and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.

≤33% OFFSET	

SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
3" × 12"	0.2316	46	10.6536	44	468.7584
12" × 24"	1.9368	7	13.5576	32	433.8432
24" × 24"	3.8736	4	15.4944	30	464.8320
2" × 2" Mosaic	0.9588	10 sheets	9.588	45	431.46
Hex 2-3/8" × 2-3/8"	0.72	10	N/A	45	450 sheets
1/2" × 11-5/8" pencil	N/A	N/A	N/A	N/A	N/A
3" × 12" SBN	N/A	N/A	N/A	N/A	N/A