



DESIGN

Tufted Pile Weight:	15.0 oz. per sq. yd. (509 g/m2)
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	7,200
Weight Density:	109,440
Stitches Per Inch:	12.5
Finished Pile Thickness:	.076
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Colorstrand® SD Nylon
Pattern Repeat:	Not Applicable
Installation Method:	Quarter Turn, Brick Ashlar, Vertical Ashlar, Multi Directional, Monolithic
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1098
Declare Label:	Declared

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static
-------------	--




521
Enduring Location



589
Innovative Touches




841
Essential Endeavor




858
Brilliant Refinement



869
Personal Style



878
Timeless Find



979
Stylish Charm