



DESIGN

Tufted Pile Weight:	38.0 oz. per sq. yd. (1288 g/m ²)
Product Type:	Modular-Walk Off
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Performance Loop Pile
Gauge:	5/32 (25.2 rows per 10 cm)
Density:	6,739
Weight Density:	256,082
Stitches Per Inch:	8.5 (33.46 per 10 cm)
Finished Pile Thickness:	.203" (5.16 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Duracolor® Premium Nylon
Pattern Repeat:	Not Applicable
Installation Method:	Quarter Turn, Monolithic, Brick Ashlar, Vertical Ashlar, Multi Directional
Soil Release Technology:	Sentry
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	44%
Post-Consumer Recycled Content:	1%
Declare Label:	Declared

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



859
Walnut



955
Cobalt



983
Iron Ore



989
Obsidian