



DESIGN

Tufted Pile Weight:	36.0 oz. per sq. yd. (1221 g/m2)
Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Cut & Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	6,545
Weight Density:	235,636
Stitches Per Inch:	12.5 (49.21 per 10 cm)
Finished Pile Thickness:	.198" (5.03 mm)
Dye Method:	Solution Dyed
Backing Material:	Unibond® Plus
Fiber Type:	Colorstrand® SD Nylon
Pattern Repeat:	72" (W) x 68.5" (L)
Width:	12' (3.66 m)
Soil Release Technology:	Sentry Soil Stain Protection
Foot Traffic Recommendation TARR:	Moderate

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 3802
Pre-Consumer Recycled Content:	39%
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static
-------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



131
Apollo



723
Tourterelle



848
Havannah



851
Congo



926
Ester Hazy




934
London Dust



938
Navarino Smoke



948
Castor



958
Oxford