## CEILINGS PLUS®

323-724-8166 323-724-8249 fax 6711 EAST WASHINGTON BOULEVARD, LOS ANGELES, CALIFORNIA 90040

www.ceilingsplus.com




## **WALLFORMS**<sup>™</sup>- Saranté<sup>®</sup>

> Formed Metal Wall Panel System

**Description:** Wallforms™ is manufactured from CNC manufacturing equipment that produces modular wall panels quickly with precision, reducing production time and lowering the overall cost of metal walls. Engineered hooks on panel flanges engage panels into preslotted flat channels allowing individual panel access.

**Finishes:** Ceilings Plus<sup>®</sup> offers a wide variety of finishes applied to aluminum. Ceilings Plus<sup>®</sup> will explore unique finish selections at therequestofthe specifier. Consult factory for possibilities.

- Aluminum with up to 85% recycled content.
- Faux Laminates Saranté<sup>®</sup>
- No VOCs
- No added urea formaldehyde
- PVC<u>Free</u>



- Width: 1' to 4' (consult factory for other dimensions).
- Length: up to 8' (consult factory for other dimensions).
- Light Weight: 1.5 lbs per sf (approx.).



**Perforations:** A variety of round, square, rectangular, and custom perforation patterns are available to meet the project requirements. See <u>Wood Perforations</u> on our website.

**Acoustics:**A variety of sound absorbing backings are available, Ceilings Plus<sup>®</sup> can supply absorbing material which can achieve NRC values ranging from .70 -.95. Noise reduction may be achieved by perforating the surface and adding an absorptive backing. Consult factory for guidance. To learn more about acoustics, see Acoustics in the <u>Learning Center</u> portion of the Ceilings Plus<sup>®</sup> web site.

**Attachment System:**Proprietary engineered and precision manufactured steel hat channels. Ensure proper panel engagement and control panel alignment. Consult factory for details.

**Fire Classification:**Wallforms<sup>™</sup> product lineis Class I, 0-25 Flame Spread as tested in accordance with ASTM E84.

Exterior: Consult factory for design information.

