

# MODERN BLISS

## Hand Stitch

Broadloom

### Construction

Tufted, Textured Loop

### Broadloom Width

13'6" (4.11 m)

### Pattern Repeat

162"W x 72"L

### Yarn Type

Universal Fibers® Silkworks SDN Type 6,6 and 6

### Stain Repel / Stain Resist / Soil Release

StainSmart®

### Antimicrobial

AlphaSan® AF Built-In Protection†

### Dye Method

Solution Dyed

### Tufted Face Weight

36 oz/yd² (1221 g/m²)

### Gauge

1/12

### Stitches Per Inch

10.0

### Tufts

120/in² (1,859/100 cm²)

### Finished Pile Height

0.19" (4.83 mm)

### Average Density (Finished)

?7600

### Standard Backing

Endura-Loc™

Available with Cushion-Loc™ attached cushion

### Nominal Total Thickness

0.31" (7.9 mm)

### Nominal Total Weight

75.0 oz/yd² (2,543 g/m²)

### Flammability (Radiant Panel ASTM-E-648)

≥ 0.45 (Class I)

### Smoke Density (NFPA-258-T or ASTM-E-662)

≤ 450

### Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)

Self-Extinguishing

### Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

### Crocking (AATCC 165)

≥ 4.0 Wet or Dry

### Static Electricity (AATCC-134) 20% R.H., 70° F.

≤ 3.5 KV, Permanent Conductive Fiber

### Texture Appearance Retention Rating (TARR)

Heavy Traffic End-Use Applications

### Recommended Maintenance

MilliCare® Textile and Carpet Care Service Network

### Indoor Air Quality—CRI Green Label Plus™

GLP8064, Carpet Category 1Y

### WARRANTIES

10 Year Face Fiber Wear

10 Year Delamination of Backing

10 Year Antistatic

10 Year Edge Ravel

5 Year Matting and Crushing

10 Year Tuft Bind

Lifetime Staining/Soiling (StainSmart®)

10 Year Colorfastness

Flammability



Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.