

MODERN BLISS

Moulage

Broadloom

Construction

Tufted, Textured Loop

Broadloom Width

13'6" (4.11 m)

Pattern Repeat

162"W x 48"L

Yarn Type

Universal Fibers® Silkworks SDN Type 6,6 and 6

Stain Repel / Stain Resist / Soil Release

StainSmart®

Antimicrobial

AlphaSan® AF Built-In Protection†

Dye Method

Solution Dyed

Tufted Face Weight

42 oz/yd² (1424 g/m²)

Gauge

1/12

Stitches Per Inch

9.5

Tufts

114/in² (1,766/100 cm²)

Finished Pile Height

0.22" (5.59 mm)

Average Density (Finished)

?7600

WARRANTIES

10 Year Face Fiber Wear
10 Year Delamination of Backing
10 Year Antistatic

10 Year Edge Ravel
5 Year Matting and Crushing
10 Year Tuft Bind

Lifetime Staining/Soiling (StainSmart®)
10 Year Colorfastness
Flammability

Standard Backing

Endura-Loc™

Available with Cushion-Loc™ attached cushion

Nominal Total Thickness

0.31" (7.9 mm)

Nominal Total Weight

80.0 oz/yd² (2,713 g/m²)

Flammability (Radiant Panel ASTM-E-648)

≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or ASTM-E-662)

≤ 450

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H., 70° F.

≤ 3.5 KV, Permanent Conductive Fiber

Texture Appearance Retention Rating (TARR)

Heavy Traffic End-Use Applications

Recommended Maintenance

MilliCare® Textile and Carpet Care Service Network

Indoor Air Quality—CRI Green Label Plus™

GLP8064, Carpet Category 1Y

