

ARX

Tergo 16

OBEX® Entrance Flooring Solutions

MODULAR GRID

Grid Material

100% UV-Resistant PVC

Grid Size

Nominal: 200 mm x 200 mm (7.87" x 7.87")

Installed Usable: 195 mm x 195 mm (7.677" x 7.677")

Nominal Total Thickness

16.0 mm (0.630")

Grid Color

Graphite

Outdoor Temperature Resistance

-22 °F to +122°F (-30°C to 50°C)

Nominal Total Weight

33.7 oz/ft² (10,283.61 g/m²)

Flammability

(BS 4790) Low Radius of Effect

Slip Resistance (BS EN B893)

Slip Resistant

Recommended Maintenance

Hot water extraction

Rolling Load Weight - Freelaid

1,102 lb. (500 Kg)

Rolling Load Weight - Glued

2,205 lb. (1,000 Kg)

ADA / BS 8300 / ISO 2152 Compliant

TEXTILE

Textile Construction

Tufted, Cut Pile

Textile Yarn Type

ECONYL® Solution-Dyed Nylon Type 6

Textile Dye Method

Solution-Dyed

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

WARRANTIES

1-Year Manufacturing Defect Warranty

5-Year Wear Warranty

This product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.