SPECIFICATION Date: 21-11-16

Sendal

MODULAR TILE

Construction Tufted, Tip Shear

Tile Size 50 cm x 50 cm (19.7" x 19.7")

Yarn Type Milliken Certified Wear-On® Nylon Type 6,6

Stain Repel / Stain Resist / Soil Release StainSmart®

Antimicrobial AlpAlphaSan® AF Built-In Protection

Dye Method Continious Dye

Tufted Face Weight 36 oz/yd² (1,221 g/m²)

Tufts* 144/in² (2,230/100 cm²)

Finished Pile Height 0.15" (3.81 mm)

Average Density (Finished) 6,980

Standard Backing PVC-Free Comfort Plus® ES Cushion

Recycled Content by Total Weight ES Backing: 26% Pre-Consumer

Nominal Total Thickness 0.394" (10.0 mm)

Nominal Total Weight 120 oz/yd² (4,069 g/m²)

Flammability (Radiant Panel Test) CRF = 7.2kW/m²; smoke = 345%.mins

Lightfastness (AATCC 16E) ≤ 4.0 at 40 Hours

Static Electricity (AATCC-134) 20% R.H.,70° F. ≤ 3.5 KV

Recommended Maintenance MilliCare® - Refer to the Ontera Cleaning &

Maintenance guide or Millicare® Australia

Indoor Air Quality Pass (ISO10580:2010.)

ACCS Grading Commercial Extra Heavy Duty and Stairs (CEHDS)

Applicable Warranties 15 year Wear Warranty

15 year Dimensional Stability warranty

15 year Anti-Static Warranty

15 Year Castor Chair Wear Warranty

Recommended Installation Method(s) Monolithic









Design Copyright - Milliken & Company

* This product utilizes Milliken's patented, high density tufting process called multiple yarn infusion. Conventional measurements of gauge and stitch rate are inadequate and misleading. Therefore, tufts per square inch are shown to provide accurate specifications

This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

