

Free Wheeling Collection



## **DESIGN**

Tufted Pile Weight: 32.0 oz. per sq. yd. (1085 g/m2)

Product Type: Broadloom Construction: Tufted

Minimum Sq. Yd.: No Minimum

Surface Texture: Level Patterned Cut & Loop 1/12 (47.00 rows per 10 cm) Gauge:

Density: 6,508 Weight Density: 208,271

Stitches Per Inch: 9.6 (37.80 per 10 cm) Finished Pile Thickness: .177" (4.50 mm) Dye Method: Solution Dyed

Backing Material: Weldlok®

Pattern Repeat: 36" (W) x 45" (L) Width: 12' (3.66 m)

Soil Release Technology: Sentry Soil Protection

Foot Traffic Recommendation TARR: Heavy

## **SUSTAINABILITY**

Fiber Type:

Green Label Plus 8216 IAQ Green Label Plus:

47% Pre-Consumer Recycled Content:

Declare Label: **Declared Red List Free** 

## **PERFORMANCE**

AATCC-134 Under 3.5 KV Static: Flammability: ASTM E 648 Class 1 (Glue Down) ASTM E 662 Less than 450

## **SERVICE**

Smoke Density:

Lifetime Limited Wear Warranty, Lifetime Static, 10 Year Limited Colorfastness to Atmospheric Warranties: Contaminants, 10 Year Stain Warranty, Lifetime

Limited Colorfastness to Light

Colorstrand® SD Nylon



711 Wonder

948

Fulfillment



859 Amazed



869 Transcendent



965 Aware



975 Legend



989 Euphoric