

Type:	
Job Name:	

Construction:

- Steel construction
- Diffuser is white smooth acrylic

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**
- Medium Base Socket (Lamp NOT included)

Notes:

- Canopy mounts to standard "J-Box"
- Custom mounting heights available
- Single ridge 15 degree swivel stem standard (1S15)
Optional cord or cable mounting, see options
- UL and CUL listed **DAMP** location
- 5-Year Warranty on LED Components



WALL

CEILING

PENDANT

OUTDOOR

WWXH 12 - 14 - 16 - 18 - 20

Height: 12" 14" 16" 18" 20"

Diameter: 12" 14" 16" 18" 20"

OAH: 24" 24" 24" 24" 36"

ORDERING INFORMATION

Example: WWXH-12-LED-A-1E26-NL-Z1-WSA-1S15

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
WWXH-12-LED		A- 120 volt	1E26 Medium Base Socket (Lamp NOT included) <i>(All Sizes)</i>	NL	B1 Satin Black T6 Pewter W2 Gloss White Z1 Satin Bronze Z3 Text Bronze	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)
WWXH-14-LED		U 120 - 277	28w LED / 3,200 lumens (114 lm per watt) <i>(All Sizes)</i>	2 3000K 4 4000K	Optional (See Price List)		1S15 - Single 15 ° Swivel Stem (Standard)
WWXH-16-LED			36w LED / 4,000 lumens (111 lm per watt) <i>(WWXH-16" - 18" - 20")</i>	Optional 3 3500K	W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver W13 Pearl Beige P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass		(Optional Suspension) (See Price List) 1S45 - Single 45 ° Swivel Stem WSJ - White "SJ" Cord BSJ - Black "SJ" Cord 1AC - Aircraft Cable w/SJ cord WSJ - White "SJ" Cord BSJ - Black "SJ" Cord
WWXH-18-LED			42w LED / 4,900 lumens (116 lm per watt) <i>(WWXH-18" - 20")</i>				
WWXH-20-LED							



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

