

Specifications

DESCRIPTION	NORM	DATA
Type de revêtement / Type of flooring		Aiguilleté plat / Flat needlefelt
Type d'enduction / Type of bonding		Enduction d'envers / Back coated
Composition des fibres de surface / Fiber composition of surface	dorix	100% Polyamide dorix® (Teint masse / Solution dyed)
Masse totale de surface / Total weight of surface	ISO 8543	500 g/m²
Masse totale / Total Weight	ISO 8543	1200 g/m²
Epaisseur totale / Total Thickness	ISO 1765	6,0 mm
Envers / Backing		Fibres synthétiques 100% recyclées / 100% recycled synthetic fibers
Dimensions / Size		200 cm lés (rouleaux/Rolls : 40 ml)
Sens de pose / Installation		Pose même sens avec recouvrement de 3 cm

Technical performances



Classification EN 1307 - 33 / Commercial Heavy

Luxury Class - LC1

Classement UPEC NF 262 - U₃₅P₃E₁C₀ (certificat n° 349TA-003.1)

Feu / Fire rating EN 13501-1 : BflS1 - CSTB Report RA07-0195



Heated Floor			Impact noise reduction			004	
	ISO 10456	0,10 m² K/W		EN ISO 10143-3	$\Delta L_{(w)} \geq 20$ dB	011	
Electrostatic prop.			Sound absorption			016	16,3%
				ISO 11654	$\alpha_w = 0,20$ (H)	017	
	ISO 6356	$\leq 2,0kV$	Colour Fastness			019	
	ISO 10965	$RT \leq 10^7 \Omega$					EN 105 - B02
Propriété dissipatrice / Dissipative Property							
Suitability for use stairs			Castor Chair			022	
	EN 1963	YES		EN 985	Passed R $\geq 2,4$	025	

Environmental issues


LEED

Répond à la démarche
HQE
