

Specifications
Tek-Wall Drift
399522

maharam

Application

Walls

Characteristics

Content: 37% Solution-Dyed Polyolefin, 32% Non-Phthalate Vinyl, 21% Solution-Dyed Post-Consumer Recycled Polyester, 10% Solution-Dyed Polyester

Finish: PFOA-Free Stain Resistant

Backing: Acrylic

Width: 54" (137cm)

Bolt Size: 50 yards (46 m)

Weight: 15 oz/ly (463 gr/lm)

Maintenance: W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Traffic: High-Suitable for all applications including heavy duty.

Country of Origin: USA

Note: Variations in color and texture are inherent to this textile.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$30.00 / C\$43.00 (FOB destination) / C\$39.50 (FOB origin)

A \$3.00/C\$4.00 per yard cutting charge applies to orders under 50 yards.

Performance

Flammability: This textile meets all appropriate flammability requirements for walls. See flame certificate for test results.

Lightfastness: 200+ Hours



Environmental

Greenguard and Greenguard Gold Certified

Contains Recycled Content

Non-Phthalate Vinyl

PFOA-Free Finish


Produced in an ISO 14001 Facility

Warranty


10 years.

© 2011 Maharam

Complete product information at maharam.com
800.645.3943




001 Batting



002 Spun



004 Gale



005 Mollusk



006 Driftwood