

Specifications
Tek-Wall View
399432

maharam

Application

Upholstered Walls, Walls

Characteristics

Content: 58% Solution-Dyed Polyolefin, 42% Solution-Dyed Post-Consumer Recycled Polyester

Finish: PFOA-Free Stain Resistant

Backing: Acrylic

Width: 54" (137cm)

Bolt Size: 50 yards (46 m)

Weight: 11 oz/ly (341 gr/lm)

Maintenance: W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Traffic: High-Suitable for all applications including heavy duty.

Country of Origin: USA

Note: Variations in color and texture are inherent to this textile. This textile can also be produced unbacked.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$29.00 / C\$41.75 (FOB destination) / C\$38.25 (FOB origin)

A \$3.00/C\$4.00 per yard cutting charge applies to orders under 50 yards.

Performance

Acoustic Rating: Upholstered Walls: ASTM C423 0.65 NRC

Flammability: This textile meets all appropriate flammability requirements for upholstered walls and walls. See flame certificate for test results.

Lightfastness: 200+ Hours



Environmental

Greenguard and Greenguard Gold Certified

Contains Recycled Content

FR Free

PFOA-Free Finish

Solution-Dyed Product

Produced in an ISO 14001 Facility

Warranty

10 years: Walls

3 years: Upholstered Walls.

© 2010 Maharam

Complete product information at maharam.com

800.645.3943




003 Conch



011 Slate



102 Drift 2



112 Luster 2



113 Reflect 2