

Mystique Specification

Construction Ultraweave Patterned Cut & Loop

Gauge 5/64

Yarn Content Antron* Lumena™ solution dyed type 6,6 nylon (SCS-EPP-01226, an Environmentally Preferable Product certified by SCS)

Yarn Type Antron® Lumena™ solution dyed nylon

Tufted Yarn Weight 22 oz./sq. yd.
Nominal Total Weight 59 oz./sq. yd.
Avg. Yarn Pile Height .125"

Average Yarn Density 6,048

Primary Back Polypropylene
Secondary Back Permian Bac™
Pattern Repeat 18.75" (W) x 48.4" (L)

Width 12'6

Custom Colors
Custom colors available at minimum yardage. Please contact your Atlas sales associate.

Folder Name Ville des Lumiéres Collection

Alternative Backing Systems This product is also available with PERMIAN BAC™ MP*, providing moisture protection.

Please view details on the Atlas website. *Trademark of Atlas Carpet Mills.

Area Rugs Area Rugs are available in a variety of shapes, sizes, backings and edge finishes. Please contact your Atlas Sales Associate for more

information on the Atlas Area Rug Program.

Pattern Match & Installation Guidelines As with all patterned carpets, a perfect match at the seams may not be obtainable. However, a reasonable pattern match may be

achieved by qualified and experienced professional installers utilizing power stretching and stay nailing techniques. All seams and cut edges must be sealed with an Atlas approved "premium low-VOC" seam sealer containing UV enhancer. Complete installation

instructions are included with each shipment and may also be viewed at atlascarpetmills.com.

General Guidelines Chair pads are highly recommended under roller casters to preserve appearance and prevent accelerated wear. Walk-off mats are

recommended at all entrances to minimize soiling. This carpet is intended only for use as a

floor covering. Atlas will not assume any liability when this carpet is used in any other manner.

Quality Assurance All certified carpets of Antron® Lumena™ solution dyed type 6,6 nylon meet strict performance and construction standards of the Invista

performance standards program assuring the highest quality carpet. The Antron® type 6,6 nylon polymer provides superior resistance to

crushing, matting, stain penetration and wear.

Soil Retardant DuraTech*, a patented soil resistance technology, is only available on styles of Antron* type 6,6 nylon.

Static Control Antron* type 6,6 nylon carries a limited lifetime antistatic protection warranty not to exceed 3.5kV.

Flammability Ratings ASTM E648 Flooring Radiant Panel Test: Class I. ASTM E662 NBS Smoke Chamber Test; < 450 in the Flaming Mode.

Indoor Air Quality Certified by the Carpet and Rug Institute and assigned the Green Label Plus certification number GLP2306.

 $NSF-140\ Certification \qquad \hbox{All Atlas carpet tiles are NSF-140 third party certified}.$

Health Product Declaration Health Product Declaration (HPD) information can be found on the Atlas website in the Resources tab under Environmental.

Environmental Product Declaration Environmental Product Declaration (EPD) information can be found on the Atlas website in the Resources tab under Environmental.

Environmental Atlas Broadloom, by total weight, contains either 10% post-consumer recycled content or 20% post-industrial recycled content. For

complete details on contributions to LEED, please visit our website at atlascarpetmills.com.

Warranty Antron® Lumena™ solution dyed type 6,6 nylon carries a Limited 10-Year Wear Warranty. See written warranties at

atlascarpetmills.com.

Additional Information Pattern lines, inherent in the pattern and construction of this product, which may be visible lengthwise or widthwise, are not considered a

manufacturing defect. Watermarking or shading, a pile reversal phenomenon that can occasionally occur in any carpet construction, regardless of fiber type, is not considered a manufacturing defect. The mill reserves the option of making minor modifications in specifications

 $when \, necessary \, in \, order \, to \, improve \, performance \, and \, to \, accommodate \, changes \, in \, material \, supply \, or \, manufacturing \, processes.$

Trademarks ©INVISTA - All Rights Reserved. Antron* and the Antron* family of marks and logos are trademarks of INVISTA.

DuraTech* is a registered trademark for soil resistant treatment. Action Bac™ is a trademark of Propex.

©Copyright This pattern is protected under federal copyright law and may not be duplicated without Atlas' express written permission.

B239