

Color Blox®

Porcelain Stone®

Color Palette



A1101 ▶ Sandbox I



A1102 ▶ Roasted Marshmallow I




A1103 ▶ Slinky I



A1104 ▶ It's a Boy! I



A1105 ▶ Yellow Brick Road IV



A1106 ▶ Limeade I



A1107 ▶ Mud Pie IV



A1108 ▶ Sea Otter I




A1109 ▶ Sidewalk Chalk I



A1110 ▶ Sea Monkey II




A1111 ▶ A Day at the Beach II




A1112 ▶ Mr. Green Jeans II




A1113 ▶ Blue Suede Shoes IV




A1114 ▶ Tree House I




A1115 ▶ Camping Out IV




A1116 ▶ Caboose II




A1117 ▶ I See the Moon II



A1118 ▶ Chocolate Candy IV



A1119 ▶ Night Night III



A1120 ▶ Grape Jelly III

Price Groups:
I = Price Group I
II = Price Group II
III = Price Group III
IV = Price Group IV

Features and Benefits

- Each color coordinates with at least 2-3 other colors
- Subtle variations in texture and shading add visual interest
- Cross-Sheen® finish for easy cleaning (available on UPS only)
- Contains a minimum of 4% pre-consumer recycled content and is manufactured by Crossville® using processes that is Green SquaredSM certified
- Made in U.S.A.



Color Blox®

Porcelain Stone®

Sizes & Finishes

Field Tile

Available in all colors

Nominal (in)	Actual (in)	Thickness (in)	Finish
6 x 6†	5-13/16 x 5-13/16	3/8	UPS
6 x 12†	5-13/16 x 11-13/16	3/8	UPS
12 x 12	11-13/16 x 11-13/16	3/8	UPS
18 x 18	17-13/16 x 17-13/16	3/8	UPS
12 x 24	11-13/16 x 23-13/16	3/8	UPS

†The cut/bevel tile is cut from larger format tile and the edges are beveled to provide a factory appearance.

Please allow two to eight weeks for delivery depending on Crossville's production schedule.

Crossville® recommends a grout joint of 3/16 to 1/4 inch.

Actual measurements stated in inches indicate tile is calibrated (non-rectified).


Actual measurements stated in mm indicate tile is rectified.

Coordinating Trim

Nominal (in)	Actual (in)	Thickness (in)	Finish
4 x 12 Single Bullnose	3-3/4 x 11-3/4	3/8	UPS
4 x 12 Bullnose Corner Left & Right	3-3/4 x 11-3/4	3/8	UPS
6 x 12 Cove Base	5-7/8 x 11-3/4	3/8	UPS
6 x 8 Cove Base Corner Left & Right	5-7/8 x 7-3/4	3/8	UPS



4 x 12 Single
Bullnose



6 x 12 Cove Base
(universal flat top)



6 x 8 Cove Base
Corner Left



6 x 8 Cove Base
Corner Right

Product Performance

Breaking Strength	>450 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.10%	ASTM C373
Scratch Hardness	6	Mohs Scale

Wet Dynamic COF

UPS	.42 – .52	DCOF AcuTest™
-----	-----------	---------------

Shade & Texture Index

Color Blox® has a shade variation of V3.



This porcelain tile product is produced with a V3 variation. Expect that the amount of color and texture on each piece may vary significantly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

Sizes (shown in A1102 Roasted Marshmallow)

12 x 24

18 x 18

6 x 12

12 x 12

6 x 6

Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment. Depending on the product, there are up to 4 widths and 7 lengths, creating more than 2,796 combinations.



Recommended Use

Color Blox® is recommended for interior floors, walls, countertops, and exterior walls in both commercial and residential applications. If offset pattern is required for tiles 18 inches or longer, Crossville® recommends an offset of not greater than 33%. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage. See CrossvilleInc.com for detailed installation instructions.

Care and Maintenance

Regular cleaning is the best way to keep Color Blox® tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

Our Warranty

Crossville Inc guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.



EcoCycle Tile Process™

Color Blox® contains a minimum of 4 percent pre-consumer recycled content and is manufactured by Crossville® using processes that recycle nearly 12 million pounds of previously discarded filtrate and fired tile waste. In addition to its own fired waste recycling, Crossville also accepts and recycles reclaimed, previously installed tile through its Tile Take-Back™ Program. For more information, visit CrossvilleInc.com/green.

Green SquaredSM Certified

Crossville® has earned Green SquaredSM certification from the Tile Council of North America (TCNA) for its entire U.S.-manufactured porcelain product line-up, as well as its manufacturing processes. The company is among the first ever recipients of this certification standard for the tile industry. TCNA developed the Green Squared certification under American National Standards Institute (ANSI) process. The multi-attribute program (ANSI A138.1) scores products in five categories of performance: product characteristics, manufacturing, corporate governance, innovation and end-of-life. Crossville's certified products and processes received stringent evaluation from Scientific Certification Systems (SCS), the green building industry's longest standing third-party certifier.

Hydrotect

Our porcelain tiles are available with Hydrotect™. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. For complete details check our website at CrossvilleInc.com.



National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

Exterior Cladding

Crossville's Porcelain Stone® Exterior Cladding Systems are suitable for virtually any conventional masonry application. When used in conjunction with our exterior cladding systems, Crossville's Porcelain Stone offers clear advantages: decreased construction costs, less site disturbance, low-to-zero maintenance after installation, accelerated construction schedules and greater strength than traditional masonry.

▶▶ Crossville® Sample Express

Sample fulfillment & Help Line
Samples@CrossvilleInc.com
1 800 221.9093

Loose Samples for
Architects & Designers

Loose Tile Samples
Sizes may vary depending on product series
Max. of 4 large field tile per order

Replacement Chips for PSS Rack
Max. of 5, 2 x 2 chips per color

Standard Shipping
UPS Ground

*Information listed here is subject to change.
Please refer to CrossvilleInc.com for the latest, most accurate information.*

Trade Organizations



Environmentally Aware

