

MAT

OBEX™ CutX

SPECIFICATION SHEET DATE: 29 APRIL 2019

Textile Construction

Tufted, Cut Pile

Custom Size

Up to 6.5 ft. wide and up to 20ft. long

Textile Yarn Type

Milliken-Certified Wearon® Nylon and Monofilament Type 6 and 6,6

Textile Dye Method

DDI (Digital Dye Infusion)

Tufted Face Weight

24 oz/yd² (814 g/m²)

Backing Type

100% PVC

Edging

100% PVC Beveled Edge

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Nominal Total Thickness

0.35" (8.8 mm)

Nominal Total Weight

12 oz/ft² (3,662 g/m²)

Flammability (ASTM E648-15e1)

0.74 (Class I)

Pill Test (ASTM D2859-15)

Pass

Recommended Maintenance

Hot Water Extraction milliCare® Textile and Carpet Care Service Network

WARRANTIES

1-Year Manufacturing Defect Warranty

5-Year Wear Warranty

This product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.