

# MAT

## OBEX™ Cut

SPECIFICATION SHEET DATE: 29 APRIL 2019

### Textile Construction

Tufted, Cut Pile

### Custom Size

Up to 6.5 ft. wide and up to 20ft. long

### Textile Yarn Type

Milliken-Certified Wearon® Nylon and Monofilament Type 6 and 6,6

### Textile Dye Method

DDI (Digital Dye Infusion)

### Tufted Face Weight

28 oz/yd<sup>2</sup> (949 g/m<sup>2</sup>)

### Backing Type

100% PVC

### Edging

100% PVC Beveled Edge

### Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

### Crocking (AATCC 165)

≥ 4.0 Wet or Dry

### Nominal Total Thickness

0.35" (8.8 mm)

### Nominal Total Weight

12 oz/ft<sup>2</sup> (3,662 g/m<sup>2</sup>)

### Flammability (ASTM E648-15e1)

0.63 (Class I)

### Pill Test (ASTM D2859-15)

Pass

### Recommended Maintenance

Hot Water Extraction or milliCare® Textile and Carpet Care Service Network

## WARRANTIES

1-Year Manufacturing Defect Warranty

5-Year Wear Warranty

This product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.