



CERTIFIED  
PORCELAIN  
TILE

# FUSION COTTO™

GLAZED PORCELAIN FLOOR & CERAMIC MOSAIC WITH REVEAL IMAGING®

FLOOR



AMERICAN OLEAN®  
PROVEN IN TILE™

AMERICANOLEAN.COM



# FUSION COTTO™

Melding old-world cotto with contemporary concrete, Fusion Cotto's nod to the enviable European look is as relevant to residential interiors as it is to commercial spaces. Reveal Imaging™ enriches its popular tone-on-tone depth of color. Meanwhile, the structured surface also provides texture for increased slip resistance. Large-format sizes come in four colors with brick-joint mosaic to complete the look. At home on floors and walls, this versatile collection spans contemporary and traditional spaces with equal ease.

Cover photo features Fusion Cotto Marrone 18 x 18 on the floor and Morello™ Moonstone 5/8 x Random mosaic on the backsplash. Above photo features Fusion Cotto Marrone 18 x 18 on the floor.



# FUSION COTTO™

GLAZED PORCELAIN FLOOR & GLAZED CERAMIC MOSAIC  
WITH REVEAL IMAGING®

## GLAZED PORCELAIN FLOOR TILE



ECRU CF11



GRIGIO CF12



MARRONE CF13



COTTO CF14

## GLAZED CERAMIC MOSAIC



ECRU CF11



GRIGIO CF12



MARRONE CF13







COTTO CF14


# FUSION COTTO™

GLAZED PORCELAIN FLOOR & GLAZED CERAMIC MOSAIC  
WITH REVEAL IMAGING®

## SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	18 x 18 Floor Tile	17-13/16" x 17-13/16" (45.20 cm x 45.20 cm)	5/16"	17.60	8
	12 x 24 Floor Tile	11-13/16" x 23-13/16" (30.00 cm x 60.48 cm)	3/8"	15.60	8
	12 x 12 Floor Tile	11-13/16" x 11-13/16" (30.00 cm x 30.00 cm)	5/16"	14.55	15
	2 x 4 Brick-Joint Mosaic ■ ■	12" x 12" Sheet (30.48 cm x 30.48 cm Sheet)	1/4"	9.96	12

## TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 12	S-43C9	30
■ Dot-mounted	□ Ceramic body			

## INSTALLATION & PRICING

### RECOMMENDED GROUT JOINT:

**Floor:** 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)

**Mosaic:** 1/8"

**RELATIVE PRICING:** Medium to High

### SHADE VARIATION



**RANDOM  
(V4)**

## PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	MOSAIC RESULT
Water Absorption	C373	< 0.5%	< 3.0%
Breaking Strength	C648	> 275 lbs.	> 250 lbs.
Scratch Hardness	MOHS	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant
Abrasion Resistance	C1027	3 (CF12, CF13, CF14) 4 (CF11)	3 (CF12, CF13, CF14) 4 (CF11)

For additional information on test results, visit us at: [americanolean.com/information/TestResults](http://americanolean.com/information/TestResults).

## USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

## APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	●*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	●*

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [americanolean.com/DCOF](http://americanolean.com/DCOF).

### APPLICATION NOTES:

Floor tile suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

Mosaic tile suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

\* Mosaic tile only

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [americanolean.com/Factors](http://americanolean.com/Factors).

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [americanolean.com/LargeTiles](http://americanolean.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit [americanolean.com](http://americanolean.com).



POST-CONSUMER  
RECYCLED MATERIALS



REVEAL IMAGING®



PRE-CONSUMER  
RECYCLED MATERIALS



MADE IN THE U.S.A.

All or select items within this series meet the requirements for these qualifications. For more information visit [americanolean.com](http://americanolean.com).



Naturally, many of our  
products can help you earn  
LEED™ credits.

888.AOT.TILE

©2017 AMERICAN OLEAN (12/17.1)



AMERICAN OLEAN®  
PROVEN IN TILE™