

# RAPPORT™

GLAZED PORCELAIN FLOOR WITH REVEAL IMAGING®

FLOOR



AMERICAN OLEAN®  
PROVEN IN TILE™

[AMERICANOLEAN.COM](http://AMERICANOLEAN.COM)



# RAPPORT™

Rapport™ glazed porcelain floor captures popular linear looks and fabric-inspired motifs in a winning design combination. Rapport features floor tile in the must-have 12 x 24 format and a color palette of four colors designed to please.

Cover and above photos feature Rapport Harmony Beige 12 x 24 on the floor.



# RAPPORT™

GLAZED PORCELAIN FLOOR WITH REVEAL IMAGING®

## GLAZED PORCELAIN FLOOR TILE

---



AGREEABLE WHITE RP03



HARMONY BEIGE RP04



CORDIAL GRAY RP05




COMPATIBLE CHARCOAL RP06




# RAPPORT™

GLAZED PORCELAIN FLOOR WITH REVEAL IMAGING®

## SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	12 x 24 Floor Tile	11-13/16" x 23-5/8" (30.00 cm x 60.00 cm)	5/16"	17.37	9

## TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 12	P-43C9A	20
	Cove Base	6 x 12	P-36C9T	22
	Cove Base Outcorner	6 x 1	PC-36C9T	15

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.  
Cove base and cove corner trim are suitable for non-freezing climates only.

## INSTALLATION & PRICING

### RECOMMENDED GROUT JOINT:

**Floor:** 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)

**RELATIVE PRICING:** Medium

### SHADE VARIATION



## PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	4

For additional information on test results, visit us at: [americanolean.com/information/TestResults](http://americanolean.com/information/TestResults).

## USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

## APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [americanolean.com/DCOF](http://americanolean.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [americanolean.com/Factors](http://americanolean.com/Factors). Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [americanolean.com/LargeTiles](http://americanolean.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit [americanolean.com](http://americanolean.com).



PRE-CONSUMER  
RECYCLED MATERIALS



REVEAL IMAGING®



MADE IN THE U.S.A.



All or select items within this series meet the requirements for these qualifications.  
For more information visit [americanolean.com](http://americanolean.com).



Naturally, many of our  
products can help you earn  
LEED™ credits.

888.AOT.TILE

©2017 AMERICAN OLEAN (08/17.1)



AMERICAN OLEAN®  
PROVEN IN TILE™