

Vitality – #7867

Construction specifications

Broadloom

Product Vitality **Style Number** 7867

Fiber Content 100% Universal Fibers® Type 6,6

with Permanent Stain Resist

Fiber Weight (tufted) 30 oz./Sq.Yd. (1017 g/m²)

Construction Pattern Loop

Gauge 1/12

Pattern Repeat 48"W x 35.25"L (121.92 cm x 89.53 cm)

Width 12′ (3.66 m)

Dve Method 100% solution dyed nylon

Pile Height .375" /.250" /.125"

(9.52 mm/6.35mm/3.18 mm)

Total Weight 64 oz./Sq.Yd. (2170 g/m²) **Primary Backing** Woven Polypropylene

Secondary Backing Woven Polypropylene with Unitary

GLP Certification GLP1678

Specifications may vary slightly over the life of a product. For current specifications, please visit www.maslandcontract.com.

Performance specifications

Warranty 10 year wear warranty

Flammability Rating Flooring Radiant Panel ASTM E-648 and/or NFPA 253

Greater than 0.45 watts/CM2 Class 1 (EU) CFL S 1

Surface Flammability of Carpets and Rugs (16 CFR Chapter II

Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859

Smoke Density Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)

Colorfastness to Light 4.0 or better

Static Rating Less than 3.5 kV. Antistat warranted for the life of the carpet

Soil Resistant Treatment A commercially durable treatment provides extra protection against soiling

Vitality meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program.

Vitality is certified GOLD by the NSF 140-2007 Sustainable Carpet Standard.

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Masland laboratory matches are obtained under cool white fluorescent lighting. Chair pads are recommended to enhance the aesthetic value and longevity of the product. All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.



^{*}For percentage of recycled content, contact your Masland Contract representative.