

## Vitality – #7867 / T7867

### Construction specifications

	<b>Broadloom</b>	<b>Modular</b>
<b>Product</b>	Vitality	Vitality
<b>Style Number</b>	7867	T7867
<b>Fiber Content</b>	100% Universal Fibers® Type 6,6 with Permanent Stain Resist	100% Universal Fibers® Type 6,6 with Permanent Stain Resist
<b>Fiber Weight (tufted)</b>	30 oz./Sq.Yd. (1017 g/m <sup>2</sup> )	28 oz./Sq.Yd. (949 g/m <sup>2</sup> )
<b>Construction</b>	Pattern Loop	Pattern Loop
<b>Gauge</b>	1/12	1/12
<b>Pattern Repeat</b>	48"W x 35.25"L (121.92 cm x 89.53 cm)	N/A
<b>Carpet Tile Size</b>	N/A	24"W x 24"L (60.96 cm x 60.96 cm)
<b>Dye Method</b>	100% solution dyed nylon	100% solution dyed nylon
<b>Pile Height</b>	.375" / .250" / .125" (9.52 mm/6.35mm/3.18 mm)	.281" / .188" / .125" (7.14 mm/4.78 mm/3.18 mm)
<b>Total Thickness</b>	N/A	.406" (10.31 mm)
<b>Total Weight</b>	64 oz./Sq.Yd. (2170 g/m <sup>2</sup> )	138 oz./Sq.Yd. (4679 g/m <sup>2</sup> )
<b>Primary Backing</b>	Woven Polypropylene	Synthetic
<b>Secondary Backing</b>	Unitary with Action-Bac	Vinyl (contains recycled content*)
<b>GLP Certification</b>	GLP1678	GLP1922

\*For percentage of recycled content, contact your Masland Contract representative.

Specifications may vary slightly over the life of a product. For current specifications, please visit [www.maslandcontract.com](http://www.maslandcontract.com).

### Performance specifications

<b>Warranty</b>	10 year wear warranty	Lifetime Commercial Limited Warranty
<b>Flammability Rating</b>	Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM <sup>2</sup> Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859	
<b>Smoke Density</b>	Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)	
<b>Colorfastness to Light</b>	4.0 or better	
<b>Static Rating</b>	Less than 3.5 kV. Antistat warranted for the life of the carpet	
<b>Soil Resistant Treatment</b>	A commercially durable treatment provides extra protection against soiling	

Vitality meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program.

Vitality is certified GOLD by the NSF 140-2007 Sustainable Carpet Standard.

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Masland laboratory matches are obtained under cool white fluorescent lighting. Chair pads are recommended to enhance the aesthetic value and longevity of the product. All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.