

PRODUCT SPECIFICATIONS

| | |
|-------------------------|--|
| Style Number | A5004 |
| Construction | High Performance Luxury Vinyl Tile |
| Wear Layer | 20 mil (0.5mm) |
| Finish | Ironclad Anti-Scratch Ceramic PU Finish (Anti-Bacterial) |
| Overall Thickness | 0.197" (5mm) |
| Reference Specification | Class III Printed Film Vinyl Tile, Type B (embossed) |

INSTALLATION

| | |
|-------------------|--|
| Installation Type | Loose Lay |
| Adhesive | Masland Premium Spray Adhesive or Masland Modular/LVT Adhesive |

PACKAGING

| | |
|---------------------|-------------------------------|
| Tile Size | 18" x 36" (45.72cm x 91.44cm) |
| Pieces per box | 6 |
| Square feet per box | 27 (2.50m ²) |
| Weight per box | 41.89lbs (19kg) |

TESTING

| TEST | STANDARD | MINIMUM REQUIREMENT | LOOSE LAY (5mm) |
|-------------------------|------------|---|----------------------|
| Dimensional Stability | ASTM F2199 | 0.02" lin. ft. max | Passes |
| Flexibility | ASTM F137 | ≤1.0" (no cracks or breaks) | Passes |
| Radiant Panel | ASTM E648 | ≥.45 watts/cm ² (NFPA Class 1) | Passes |
| Residual Indentation | ASTM F1914 | Avg. <8% | Passes |
| Resistance to Heat | ASTM F1514 | ΔE < 8 avg. max | Passes |
| Resistance to Light | ASTM F1515 | ΔE < 8 avg. max | Passes |
| Resistance to Chemicals | ASTM F925 | No more than slight change | Passes |
| Size Tolerance | ASTM F2421 | ±0.016"/lin. ft. | Passes |
| Slip Resistance | ASTM D2047 | ADA Compliant | Passes |
| Smoke Density | ASTM E662 | ≤450 | Passes |
| Static Load | ASTM F970 | 250 psi min | Passes |
| Thickness Tolerance | ASTM F386 | ±0.005" | Passes |
| Indoor Air Quality | | Low VOC | FloorScore Certified |

WARRANTY

| | |
|------------------|--|
| Commercial | 10 Year - Limited Commercial Wear Warranty |
| Light Commercial | 15 Year - Limited Commercial Wear Warranty |

See warranty documentation for full details of terms and conditions.

