

## Burst – #T7906

### Construction specifications

---

<b>Product</b>	Burst
<b>Style Number</b>	T7906
<b>Fiber Content</b>	100% Universal Fibers® Type 6,6 with Permanent Stain Resist
<b>Fiber Weight (tufted)</b>	24 oz./Sq. Yd. (814 g/m <sup>2</sup> )
<b>Construction</b>	Tip Sheared Loop Pattern
<b>Gauge</b>	1/12
<b>Carpet Tile Size</b>	24"W x 24"L (60.96 cm x 60.96 cm)
<b>Dye Method</b>	100% solution dyed nylon
<b>Pile Height</b>	.375" / .250" / .125" (9.53 mm / 6.35 mm / 3.18 mm)
<b>Total Thickness</b>	.375" (9.53 mm)
<b>Total Weight</b>	138.48 oz./Sq. Yd. (4696 g/m <sup>2</sup> )
<b>Primary Backing</b>	Synthetic
<b>Secondary Backing</b>	EarthWise (non-phthalate/contains recycled content*)
<b>GLP Certification</b>	GLP1922

\*For percentage of recycled content, contact your Masland Contract representative.

Specifications may vary slightly over the life of a product. For current specifications, please visit [www.maslandcontract.com](http://www.maslandcontract.com).

### Performance specifications

---

<b>Warranty</b>	Lifetime Commercial Limited Warranty
<b>Flammability Rating</b>	Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM <sup>2</sup> Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
<b>Smoke Density</b>	Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)
<b>Colorfastness to Light</b>	4.0 or better
<b>Static Rating</b>	Less than 3.5 kV. Antistat warranted for the life of the carpet

Tufted fiber weight denotes specs prior to tip shearing. Tip Shearing removes a small amount of fiber, which will vary slightly by product and production run.

Burst meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program.

Burst is 3<sup>rd</sup> party certified by the NSF-140 Sustainable Carpet Standard.

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Masland laboratory matches are obtained under cool white fluorescent lighting. Chair pads are recommended to enhance the aesthetic value and longevity of the product. All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.