



Construction specifications

Product	Dividend
Style #	7233
Fiber Content	Antron® Legacy nylon
Fiber Weight (tufted)	32 oz./Sq. Yd. (1085 g/m ²)
Construction	Loop Pattern
Pattern Repeat	2" W x 2" L (5.08cm x 5.08cm)
Dye Method	Beck Dyed
Gauge	1/12
Width	12' (3.66)
Pile Height	.250" / .125" (6.35mm/3.18mm)
Total Weight	78 oz./Sq. Yd. (2644 g/m ²)

Performance specifications

Flammability Rating:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts / CM ² Class 1. (EU) CFL S1
Smoke Density:	Passes NBS Smoke Chamber Test ASTM E-662
Colorfastness	4.0 or better
Static Rating:	Less than 3.5 kV
Warranty:	10 year warranty
Primary Backing	Woven Polypropylene
Secondary	Woven Polypropylene
DuraTech® Soil Resistant Treatment:	A commercially durable treatment provides extra protection against soiling.

This product is certified GOLD by the NSF 140-2007 Sustainable Carpet Standard.



Dividend meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Certification # GLP2950.

All Masland Designs are protected under the U. S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.