



## **Construction specifications**

Product	Runway Tile
Style #	T301
Fiber Content	Antron Lumena® nylon
Fiber Weight (tufted)	22 oz./Sq. Yd. (746 g/m <sup>2</sup> )
Construction	Loop Pattern
Carpet Tile Size	24" x 24" (60.96cm x 60.96cm)
Dye Method	Solution Dyed
Gauge	1/12
Pile Height	.250"/.188"/.125" (6.35mm/ 4.78mm/ 3.18mm)
Total Weight	148 oz./Sq. Yd. (5018 g/m <sup>2</sup> )
Installation	Quarter turn recommended for optimum installation appearance. Alternative installation methods should be tested for aesthetic effect.

## **Performance specifications**

Flammability Rating:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts / CM <sup>2</sup> Class 1. (EU) CFL S1
Smoke Density:	Passes NBS Smoke Chamber Test ASTM E-662
Colorfastness	4.0 or better
Static Rating:	Less than 3.5 kV
Warranty:	Lifetime Limited Warranty
Primary Backing	Synthetic
Secondary	Vinyl
DuraTech® Soil Resistant Treatment:	A commercially durable treatment provides extra protection against soiling.

This product is certified PLATINUM by the NSF 140-2007 Sustainable Carpet Standard.



Runway meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Certification # GLP1922.

All Masland Designs are protected under the U. S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.