

Shire – 7973

Construction specifications

Product	Shire
Style Number	7973
Fiber Content	100% Solution Dyed Polyester BCF
Fiber Weight (tufted)	30 oz./Sq.Yd. (1017 g/m ²)
Construction	Cut Pile
Pile Height	.469" (11.91 mm)
Gauge	5/32
Pattern Repeat	None
Dye Method	Solution Dyed
Total Weight	67 oz./Sq.Yd. (2272 g/m ²)
Primary Backing	Woven Polypropylene
Secondary Backing	Action Bac
GLP Certification	GLP2385

Specifications may vary slightly over the life of a product. For current specifications, please visit www.maslandcontract.com.

Performance specifications

Warranty	10 year limited wear warranty
Flammability Rating	Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) CFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density	Passes NBS Smoke Chamber Test ASTM E-662
Colorfastness to Light	4.0 or better
Static Rating	Less than 3.5 kV. Antistat warranted for the life of the carpet

Shire meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program.

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Masland laboratory matches are obtained under cool white fluorescent lighting. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.

