Assembly Instructions

KI 700 Series Cupboard Door Installation

May 1999

KI Pembroke P.O. Box 580 1000 Olympic Drive Pembroke, Ontario K8A 6X7

TEL (613) 735-5566 FAX (613) 735-3333

Components

- 1 Cabinet
- 2 Door Hinges 3 Hinge Mounting Plates
- 4 Cupboard Door


Tools Required

Phillips Screwdriver

Hardware Parts List

(8 - 16)* #20161 - #8 x 1/2" Screws (8 - 16)* #20171 - #10 x 1/2" Screws


*(8) screws for units up to 39 1/4" *(16) screw for units 40 25/32" and up



Installing Cupboard Doors

- 1. Insert cupboard door hinges into 1 3/8" holes in door. Secure each in place with (2) #8 x 1/2" screws.
- 2. Position hinge mounting plates on front uprights at corresponding height to hinges in doors. Attach mounting plates using (2) #10 x 1/2" screws.
- 3. Loosen pre-installed screw in hinge mounting plates. With hinges in open position, place the door hinges over the mounting plates, Figure A. Slide the door/hinge back and tighten the loosened screws in the mounting plates to see the door than the plant to be seen the door than the plant to be seen the door than the seen the door than the seen the seen the door than the seen the seen the seen that the s plates to secure the door/hinge in place, Figure B.







Assemble units as described herein only. To do otherwise may result in instability. All screws, nuts and bolts must be tightened securely and must be checked periodically after assembly. Failure to assemble properly, or to secure parts may result in assembly failure and injury.