


ETC130

Inground Luminaires

1/10



we-ef



Description

IP67. Inground uplight. Suitable for flush installation in concrete or earth. Special effects and distributions can be realized with linear lens, flood lens, 6° directional lens, 20° directional lens, or color filters.

ETC130

Inground Luminaires

2/10



we-ef

Specifications

Material Specification

Body:	Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.
Lens:	5/8" thick clear tempered glass lens. Max. load 5 tonnes.
Colours:	 Stainless Steel
Gasket:	Silicone rubber gasket
Fasteners:	PCS polymer coated stainless steel
Ingress protection:	IP67
Impact protection:	IK10+
Corrosion protection:	5CE
Mounting:	Suitable for installation in concrete or earth. Suitable for walk-over and drive-over applications. Proper drainage and foundation support must be provided.
Listings:	UL, c UL listed. Suitable for wet locations.

Electrical Specification

Power supply:	Integral [ECG] electronic MH ballast for 120 or 277 volt supply. Specify voltage.
Driver / Ballast:	Integral HPF or ECG control gear
Termination:	Factory sealed termination chamber
Cable:	3 feet of flexible 18/3 cable

Ambient Temperature

Ta less than 25 deg. C

ETC130

Inground Luminaires

3/10



Choices

Light Distributions	Lumens	Wattages	Colour Temperatures	Colours
 symmetric, medium beam [M]	3300	35	 3000K	 Stainless Steel
 symmetric, very narrow beam [VN]				
 wallwash				
 asymmetric, very narrow beam				

ETC130

Inground Luminaires

4/10



Configurations

Light Distributions	Part ID	Light Source	Lumen	Gear	Weight	Link
 symmetric, medium beam [M]	611-3050	CMH39 T-6/ G-12 base	3300	electronic gear	16.00	 
 symmetric, very narrow beam [VN]	611-3051	CMH39 T-6/ G-12 base	3300	electronic gear	16.00	 
 asymmetric, very narrow beam	611-3051 611-8138	CMH39 T-6/ G-12 base	3300	electronic gear	16.00	 



Configurations

Light Distributions	Part ID	Light Source	Lumen	Gear	Weight	Link
 wallwash	611-3050 611-8139	CMH39 T-6/ G-12 base	3300	electronic gear	16.00	

Related Families / ETC100

Family		Dimensions	Wattage	Lumen	Links	
					Links	Download Data Sheet
ETC109 LED		2.56	0 W	4 -18		
ETC119 LED		3.74	1 W	80		
ETC110-3 LED		3.74	3 W	404		




Optical Accessories

Concentric louvre

C1


■ 611-8232 Concentric louvre IR for [EE]

6.26



CTA® Cool Touch Adaptor

■ 611-8030 Cool Touch Adapter CTA



ETC130


Inground Luminaires

7/10




Directional lens

	C1
■ 611-8138 Directional lens 10-6°	6.26



	C1
■ 611-8139 Directional lens 10-20°	6.26



ETC130


Inground Luminaires

8/10



Flood lens

	C1
■ 611-8137 Flood lens IO-360	6.26



Linear louvre

	C1
■ 611-8230 Linear louvre IL for [B] and [M]	6.26



ETC130

Inground Luminaires

9/10




Linear spread lens

C1

611-8136 Linear spread lens IO-180

6.26




Source shield

C1

611-8231 Source shield IQ

6.26



Electrical Accessories

ETC130

Inground Luminaires

10/10



Sealable junction box

	C1	M1	M2
■ 697-8072 Sealable junction box SJB 130	5.75	Ø 0.39	Ø 0.47 - 0.75

