



ETC120-GB LED ASC

Inground Luminaires

1/7



we-ef



Description

IP67. Inground uplight. Suitable for flush installation in concrete or earth. Special effects and distributions can be realized with linear lens, flood lens, 6° directional lens, 20° directional lens, or color filters.

ETC120-GB LED ASC

Inground Luminaires

2/7



we-ef

Specifications

Material Specification

Body:	Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.
Lens:	5/8 in thick Antislip Coating ASC tempered glass lens (Slip Resistance Class R10), max load 5 tonnes
Colours:	 Stainless Steel
Gasket:	Silicone rubber gasket
Fasteners:	PCS polymer coated stainless steel
Ingress protection:	IP67
Impact protection:	IK10+
Corrosion protection:	5CE
Mounting:	Suitable for installation in concrete or earth. Suitable for walk-over and drive-over applications. Proper drainage and foundation support must be provided.
Listings:	ETL listed. Suitable for wet locations.

Electrical Specification

Power supply:	Integral [ECG] LED driver provides 120-277 volt range.
Termination:	Factory sealed termination chamber
Cable:	3 feet of flexible 18/3 cable

Lifetime

LED >60,000 h Ta 25°(L70/B10) Control gear >50,000 h Ta 25°

ETC120-GB LED ASC

Inground Luminaires

3/7



Choices

Light Distributions	Lumens	Wattages	Colour Temperatures	Colours
 symmetric, medium beam [M]	738	6	 3000 K	 Stainless Steel
 symmetric, very narrow beam [VN]			 4000 K	
 symmetric, very narrow beam, 'sharp cut-off' [VNS]				

ETC120-GB LED ASC

Inground Luminaires

4/7



Configurations

Light Distributions	Part ID	Light Source	Lumen	Gear	Weight	Link
 symmetric, medium beam [M]	611-2226	LED-3/6W / 700 mA - 3000 K	738	electronic gear	10.30	
	611-2227	LED-3/6W / 700 mA - 4000 K	738	electronic gear	10.30	
 symmetric, very narrow beam [VN]	611-2228	LED-3/6W / 700 mA - 3000 K	738	electronic gear	10.30	
	611-2229	LED-3/6W / 700 mA - 4000 K	738	electronic gear	10.30	

ETC120-GB LED ASC

Inground Luminaires


5/7



Configurations

Light Distributions	Part ID	Light Source	Lumen	Gear	Weight	Link
 symmetric, very narrow beam, 'sharp cut-off' [VNS]	611-2230	LED-3/6W / 700 mA - 3000 K	738	electronic gear	10.30	
	611-2231	LED-3/6W / 700 mA - 4000 K	738	electronic gear	10.30	

Related Families / ETC100-GB ASC

Family		Dimensions	Wattage	Lumen	Links	
					Links	Download Data Sheet
ETC120-GB LED ASC		6.3	6 W	738		
ETC130-GB LED ASC		9.84	18 W	2217		
ETC140-GB LED ASC		11.81	24 W	3228		

ETC120-GB LED ASC

Inground Luminaires


6/7



Optical Accessories


Flood lens

	C1
611-8027 Flood lens IO-360	2.36



Honeycomb louvre

	C1
611-8224 IW-ETC120_GB_LED Honeycomb louvre	2.89



ETC120-GB LED ASC


Inground Luminaires

7/7



Linear spread lens

	C1
■ 611-8028 Linear spread lens IO-180	2.36



Electrical Accessories

Sealable junction box

	C1	M1	M2
■ 697-8072 Sealable junction box SJB 130	5.75	Ø 0.39	Ø 0.47 - 0.75

