


ETC140-GB-CC LED

Inground Luminaires

1/11



we-ef



Description

RGBW/RGBA Colour Changer. IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1.5 m of flexible PVC free cable. Cable gland with spiral cable bending protection. Integral EC electronic converter in thermally separated compartment. 'No tool' removable gear/lens tray. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. DMX interface. Gimbal mounted, 360° rotatable and 30° tiltable. The optional installation blockout is recommended for mounting. To be ordered separately. Optional with Anti-Slip ceramic Coating ASC to DIN 51130 (Trip Classification 10) available on request.

ETC140-GB-CC LED

Inground Luminaires

2/11



we-ef

Specifications

Material Specification

Body:	Stainless steel construction
Lens:	Safety glass lens; max. load 5 tonnes
Colours:	 Stainless Steel
Gasket:	Silicone rubber gasket
Fasteners:	PCS Polymer Coated Stainless Steel Hardware
Ingress protection:	IP67
Impact protection:	IK10+
Surge protection:	1/2 kV (optional SP10)
Mounting:	The optional installation blockout is recommended for mounting
Listings:	Please contact WE-EF for UL/ETL Listing Status.

Electrical Specification

Power supply:	Integral [ECG] LED driver provides 120-277 volt range.
Power factor:	> 0.9
Driver / Ballast:	Integral EC electronic converter
Cable:	3 feet of flexible 18/3 cable

Lifetime

LED >60,000 h Ta 25°(L70/B10) Control gear >50,000 h Ta 25°

ETC140-GB-CC LED

Inground Luminaires

3/11



Choices

Light Distributions	Lumens	Wattages	Colour Temperatures	Colours
 symmetric, wide beam [W]	2592	30	 RGBW	 Stainless Steel
 symmetric, medium beam [M]	3000		 RGBA	
 wallwash				

ETC140-GB-CC LED

Inground Luminaires

4/11



Configurations

Light Distributions	Part ID	Light Source	Lumen	Gear	Weight	Link
 symmetric, wide beam [W]	611-4080	LED-24/30W - RGBW/4K	3000	electronic gear	29.90	
	611-4082	LED-24/30W - RGBA	2592	electronic gear	29.90	
 symmetric, medium beam [M]	611-4079	LED-24/30W - RGBW/4K	3000	electronic gear	29.90	
	611-4083	LED-24/30W - RGBA	2592	electronic gear	29.90	

ETC140-GB-CC LED

Inground Luminaires

5/11



Configurations

Light Distributions	Part ID	Light Source	Lumen	Gear	Weight	Link
 wallwash	611-4081	LED-24/30W - RGBW/4K	3000	electronic gear	29.90	
	611-4085	LED-24/30W - RGBA	2592	electronic gear	29.90	

Related Families / ETC100-GB-CC

Family		Dimensions	Wattage	Lumen	Links	
					Links	Download Data Sheet
ETC130-GB-CC LED		9.84	19 W	1620 -1920		
ETC140-GB-CC LED		11.81	30 W	2592 -3000		

ETC140-GB-CC LED

Inground Luminaires


6/11




Electrical Accessories

Sealable junction box

	C1	M1	M2
■ 697-8072 Sealable junction box SJB 130	5.75	Ø 0.39	Ø 0.47 - 0.75



	C1
■ 611-3029 Sealable junction box SJB with DMX in/out	5.74



ETC140-GB-CC LED

Inground Luminaires

7/11



we-ef

Control

DMX Controller

■ **400-9001** DMX Controller



DMX Splitter

■ **400-9005** DMX Splitter



ETC140-GB-CC LED

Inground Luminaires

8/11



we-ef

DMX Booster Box

■ **400-0364** DMX Booster Box for DMX cable system



DMX Motion Sensor

■ **400-9011** DMX Motion Sensor



ETC140-GB-CC LED

Inground Luminaires

9/11



we-ef

DMX Wireless Transceiver

■ **400-9009** DMX Wireless Transceiver



DMX Wireless Repeater

■ **400-9010** DMX Wireless Repeater



ETC140-GB-CC LED

Inground Luminaires

10/11



we-ef

DMX Controller (smart)

■ **400-9002** DMX Controller (smart)



DMX Controller (smart) - RDM ready

■ **400-9004** DMX Controller (smart) - RDM ready



ETC140-GB-CC LED

Inground Luminaires

11/11



we-ef

DMX Controller - RDM ready

■ **400-9003** DMX Controller - RDM ready

