

STP204 LED

Recessed Wall Luminaires

1/5




we-ef



Description

IP55. Recessed LED steplight for orientation. Suitable for installation in cavity wall construction or concrete pour construction using optional installation blockout.



STP204 LED

Recessed Wall Luminaires

2/5



we-ef

Specifications

Material Specification

Body:	Luminaire body and lens frame constructed in die cast aluminum.
Lens:	Prismatic polycarbonate lens.
Colours:	RAL9004 Black RAL9007 Grey Metallic RAL9016 White RAL8019 Dark Bronze
Gasket:	Silicone rubber gasket
Fasteners:	PCS polymer coated stainless steel
Ingress protection:	IP55
Impact protection:	IK10
Corrosion protection:	5CE
Surge protection:	1/2 kV
Mounting:	Suitable for installation in cavity wall construction or concrete pour construction using optional installation blockout.
Listings:	ETL listed. Suitable for wet locations.

Electrical Specification

Power supply:	Integral [ECG] electronic 0-10 V dimmable driver in 120 or 277 volt. Specify voltage.
Driver / Ballast:	Integral EC electronic converter
Cable:	Suitable for through wiring.

Lifetime

LED >60,000 h Ta 25°(L70/B10) Control gear >50,000 h Ta 25°

STP204 LED

Recessed Wall Luminaires

3/5



Choices

Light Distributions	Lumens	Wattages	Colour Temperatures	Colours
 asymmetric, forward-throw [A60]	538	4	3000 K 4000 K	RAL9004 Black RAL9007 Grey Metallic RAL9016 White RAL8019 Dark Bronze

STP204 LED

Recessed Wall Luminaires

4/5



Configurations

Light Distributions	Part ID	Light Source	Lumen	Gear	Weight	Link
	615-0721	LED-4/4W / 350 mA - 3000 K	538	electronic gear	2.00	
	615-0720	LED-4/4W / 350 mA - 4000 K	538	electronic gear	2.00	

Related Families / STP200

Family		Dimensions	Wattage	Lumen	Links	
					Links	Download Data Sheet
STP204 LED		8.07 x 3.62	4 W	538		
STP254 LED		9.84 x 3.62	6 W	807		

STP204 LED

Recessed Wall Luminaires

5/5



we-ef

Mounting Accessories

Installation blackout

C1

■ **615-9320** Installation blackout BST20-I

4.53

