



## DESIGN

Product Type:	Glue Down LVT
Overall Thickness:	2.5 mm (.1")
Wear Layer:	20 mil (0.5 mm)
Finish:	M-Force Ultra
Surface Profile:	Wood Emboss / Embossed-in-Register
Edge Profile:	Microbevel
Size:	228.6mm x 1219.2mm (actual) 9"W x 48"L (nominal)
Square Feet Per Carton:	36 sf/ctn (3.34 m <sup>2</sup> /ctn)
Pieces Per Carton:	12 pieces/ctn
Pounds per carton:	33 lbs/ctn (15.56 kg/ctn)
Installation Method:	Glue Down
Recommended Adhesive:	M95.0 Resilient Flooring Adhesive, M99 Resilient Flooring Adhesive, or M700 Adhesive
Underlayment:	Mohawk Accusound

## PERFORMANCE


Construction:	Commercial Grade Enhanced Dryback Resilient Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size and Tolerance:	ASTM F2055 - Passes - $\pm 0.016$ in. per linear foot
Thickness:	ASTM F386 - Passes - Nominal $\pm 0.005$ in
Flexibility:	ASTM F137 - Passes - 1" mandrel
Dimensional Stability:	ASTM F2199 - Passes - $\leq 0.024$ in. per linear foot
Static Load:	ASTM F970 - Passes, modified - 1500 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Resistance To Chemicals:	ASTM F925 - Passes - No Change or Slight Change
Resistance To Light:	ASTM F1515 - Passes - $\Delta E \leq 8$
Resistance To Heat:	ASTM F1514 - Passes - $\Delta E \leq 8$
Critical Radiant Flux:	ASTM E648 - Passes - $\geq 0.45$ watts/cm <sup>2</sup> , Class 1
Smoke Density:	ASTM E662 - Passes

## SUSTAINABILITY


Certification:	FloorScore® certified
----------------	-----------------------

## SERVICE

Warranties:	Limited 10 Year Commercial Warranty
-------------	-------------------------------------




131  
Bisque  
Quickship Available




152  
French Oak  
Quickship Available




311  
Alabaster  
Quickship Available



353  
Burl  
Quickship Available



931  
Nimbus  
Quickship Available



989  
Cassolette  
Quickship Available