



www.interceramic.com





A white canvas that attracts elegance and openness, while its brightness and reflection create a unique space atmosphere. Pure. Tranquil. Serene.





Ideal for all residential and light commercial floor and wall applications.

HD Ceramic Floor & Glazed Rectified Ceramic Wall Tile CERAMIC STS L PEI III









## Colors

Floor



white

Floor sizes

20 x 20 in

10 x 20 in

Floor Decos











4 x 20 in

Floor Trim

Surface Bullnose 3 x 20 in



Wall

white glossy

white matte

Wall sizes

12 x 24 in

4 x 24 in

Wall Decos



Cuisine Listel Rectified 10 x 24 in



Circular Mosaic Listel Rectified 4 x 24 in





## Testing Results

| Floor                   |            |            |
|-------------------------|------------|------------|
| Wear Rating             | III        | PEI        |
| Coefficient of Friction | < 0.60     | ASTM C1028 |
| Water Absorption        | 2.50%      | ASTM C373  |
| Scratch Hardness        | 7.0        | MOHS Scale |
| Breaking Strength       | 450 lbs    | ASTM C648  |
| Frost Resistance        | Resistant  | ASTM C1026 |
| Recycle Content         | 20%        | N/A        |
| Thickness               | 10.8 mm    | N/A        |
| THICKHESS               | 10.0 11111 | IV/A       |

| Wall                |           |            |
|---------------------|-----------|------------|
| Water Absorption    | 16.0%     | ASTM C3737 |
| Breaking Strength   | 125 lbs   | ASTM C648  |
| Chemical Resistance | Resistant | ASTM C650  |
| Bonding Strength    | 70 psi    | ASTM C482  |
| Crazing Resistance  | Resistant | ASTM C424  |
| Recycle Content     | 10%       | N/A        |
| Thickness           | 8.15 mm   | N/A        |



For more information about qualifying LEED points please visit: www.interceramicgreen.com

