

USAGE INFORMATION

TILE APPLICATIONS	RESIDENTIAL	LIGHT COMMERCIA
Floors		SALES EL ALEXANIII
Walls/Backsplashes		
Countertops	The Part of the Pa	
Exterior		No. of Concession, Name of Street, or other Persons, Name of Street, or ot
PLEASE NOTE: Not recommended for ramps or	r floor areas exposed to water or heav	yy grease ac

TECHNICAL INFORMATION

TEST	RESULTS	ANSI STANDARDS	ASTM#
Abrasion Resistance (PEI)	Class III	Class 0-V	ASTM C1027
Chemical Resistance	Resistant	As Reported	ASTM C650
Bonding Strength (psi)	>50 psi	≥50 psi	ASTM C482
Dynamic Coefficient of Friction (DCOF)*	<0.42	As Reported	ANSI A 137.1-2012
Scratch Hardness	5.0	MOHS 1-10	MOHS Scale
Water Absorption	<3.0%	3.0% - 7.0%	ASTM C373
Breaking Strength	>300 lbf.	>250 lbf.	ASTM C648
Frost Resistance	Resistant	As Reported	ASTM C1026
Stain Resistance	Resistant	As Reported	ASTM C1378
Crazing Resistance	Resistant	As Reported	ASTM C424
Thermal Shock	Resistant	As Reported	ASTM C484
Recycled Content (Pre-Consumer)	19.20%	N/A	N/A
Recycled Content (Post-Consumer)	11.40%	N/A	N/A

*It is important to note that Dynamic Coefficient of Friction results can vary after installation due to the presence of foreign materials, such as water, oil and other materials the length of the human stride at the time of slip; type of floor finish and condition of shoe sole.

Ø G+ ☑ 🛱 🗗 🛩

CEMENTINE

Durabody Ceramic Floor Tile

Interceramic

CRAFTED FOR LIFE





































16"x16"

16"x16"







ANTIQUE MIX (1 SKU 4 different faces)














16"x16"



























16"x16"

CONTRAST DECORATIVE ACCENTS





ANTIQUE DECORATIVE ACCENTS















8"x8"

Quadrati Corner Catena Corner

Variation Rating: MODERATE Light to moderate shade and texture variation with in each carton













SIZES