



BTW Better Than Wood

Ceiling and Wall Paneling

BTW CEILING



>> **Cost effective**, maintainable biophilic element that **mimics natural materials**.

>> Simulates the **rich color, grain and warmth** of real wood.

AND WALL PANELING



>> Lasting wood aesthetic and ambience.

>> Superior acoustic qualities.

>> Better-than-wood benefits at a **fraction of the cost.**

SPECIFICATIONS

FINISH OPTIONS



Cherry

Gum wood

Walnut

Blonde Ash

Espresso

Barn wood

APPLICATIONS

- 2x2 ceiling grid
- 2x4 ceiling grid
- Drywall ceiling
- Drywall paneling

COMPOSITION

- PET (polyethylene terephthalate) - Polyester fibers are combined with high melt and low melt fibers. A stitching process weaves these fibers together in conjunction with heat and pressure, which forms into a board.
- Vinyl - Thick graphic vinyl. 0.25mm
- Adhesive - Hot Melt PUR: Kleiberit 702.8

SOUND ATTENUATION PERFORMANCE

- Unique, microperforated finish offers superior acoustic performance not found in most faux wood.



Test	Result
CAC	25
STC	63
NRC	.30
IIC	70

DIMENSIONS

- L = 86.5 inches / 2200mm
- W = 7.8 inches / 200mm
- T = .5 inches / 12mm

FIRE PERFORMANCE

- Class A available (optional)

ASTM TESTING DATA

(full reports upon request)

- ASTM-E1414
- ASTM-E413-16
- ASTM E90
- ASTM E492
- ASTM C423

PERIMETER TRIM

- Black anodized aluminum

T-BAR

- Retrofit drop ceiling tiles by adhering perimeter trim to existing T-Bar grid, and then using Snap Clips to attach BTW planks to T-Bar grid.

