

The articulating monitor arm's range and flexibility reduces eye and wrist injuries, while the laptop's suspension from the work surface protects it from spills and other common mishaps.

Single Arm Options















Technical Specification

- Thermo-fused polyester finish
- High pressure die cast aluminum construction
- Conforms to VESA 75mm x 75mm, 100mm x 100mm and 100mm x 200mm mounting patterns
- 5.25" range of vertical movement
- 40 degrees of tilt (20 degrees+/20 degrees)
- 360 degree monitor rotation
- 360 degree arm rotation
- Tablet Mount for tablet applications
- Quick Change Mount and Direct Mount for monitor application
- Mounts available: Bolt through, C-Clamp.



Dual Arm Options



SpaceArm Double Hub SA012



SpaceArm Extended Double Hub SA012XP



Sit Stand SpaceArm Double Hub SS012



SpaceArm Long Double Hub SX012



SpaceArm Extended Double Hub SA012XP

Enviromental Design Attributes

SpaceArm

- Recycled content of aluminum 100%
- Recyclable aluminum after use 100%

Cardboard Packaging

- Recycled content 20%
- Recyclable after use 100%

Pulp Tray

- Recycled content 100%
- Recyclable after use 100%

Plastic Packaging

- Low density polyethylene
- Recycled content 30%
- Recyclable after use 100%

Benefits

- Security Keep your monitors and tablets safe with anti-theft features.
- Positioning Easy access and alignment for multiple monitor or tablet applications.
- Organization Easy access and alignment for multiple monitor or laptop application.
- Ergonomic A wide range of adjustments puts your monitor in the most comfortable position for your needs.
- Space Increases work surface efficiencies by positioning the monitor or tablet on an arm making wasted space usable.
- Technology Flexible and adaptable for the inevitable change.



Mounting Options



We also carry a number of vertical mounts from manufacturers such as Steelcase, Allsteel, Haworth, Teknion, Knoll, Herman Miller, DIRTT and others. To learn more, please visit our web site.

Colour Options



Technical Specs

- Thermo-fused polyester finish
- High pressure die-cast aluminium •
- construction
- 5-axis position adjustment
- Conforms to VESA 75mm x 75mm,
- 100mm x 100mm and 100mm x
- 200mm mounting patterns
- 40 degrees of tilt
- (20 degrees+/20 degrees-)
- 360 degree monitor rotation

- 360 degree arm rotation
- 2.5" (63.5mm) depth in the folded position
- 4" (355.6mm) of travel 7"+ (177.8mm) above the centre of hub and 7"-(177.80mm) – below the centre of hub)
- Gas spring standard 5-16lbs (2.67kg-7.25kg)
- Gas spring options, 2-10lbs (.90kg-4.53kg) and 15-32lbs (6.8kg 14.51kg)
- Quick Change Mount and Direct Mount for monitor application
- Mounts available: Bolt through, C-Clamp, Large C-Clamp, Grommet, Single Resolve, Double Resolve, Race, Wall, Column, SpaceBeam 1, SpaceBeam 2, Adjustable Slatwalls and a multitude of panel system brackets.