

S-700 Floor Tile Adhesive — Thin Spread



CAUTION

S-700

EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Vinyl Composition Tile
- BioBased Tile

DESCRIPTION:

Type:	Water-based/asphalt-rubber
Color:	Black
Taggants:	Contains no visible taggants
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	350–400 sq. ft./gallon (32–37 sq. m)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Until dry to touch; approximately 30 minutes or more
Working Time:	18 hours (May vary based on job conditions, substrates, temperature and humidity)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	Zero g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet — clean, white cloth with neutral detergent and water Dry — clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, ceramic, terrazzo and marble; polymeric poured floors, suspended wood and wood underlayments; steel, stainless steel, aluminum, lead, copper, brass and bronze; properly mixed and applied powdered underlayment; primed and poured-in-place gypsum subfloors; radiant-heated subfloors where the surface temperature does not exceed 85° F (29° C).
Advantages:	Moisture and alkali resistant AGIS Guarantee Nonflammable, ammonia-free, and low odor Contains low or no organic solvents Can be used over “cutback” adhesive residue (reduces subfloor prep)