Inspiring Great Spaces®



Product Declaration Health and Environmental Luxury Vinyl Tile (Solid Vinyl Tile)

Luxury Vinyl (LVT)

Product Declaration



Hen House Market, Kansas City, MO Jeff Maple Design

Committed to Sustainability.

Armstrong Flooring is committed to delivering solutions that reduce the environmental impact of the buildings you create, from product design and raw material selection, to how our products are produced and delivered.

This Product Declaration documents the following:

- Product ingredients
- Ingredient screening
- Life Cycle Assessment (LCA) Summary
- VOC Emissions and VOC content information
- Environmental certifications
- Performance attributes

LVT is designed to be durable, beautiful and easy to install, making it a great product for commercial applications.

Global Warming Potential (kg CO ₂ equivalent) Acidification Potential (kg SO ₂ equivalent) Eutrophication Potential (kg PO ₄ ³ equivalent) Ozone Depletion Potential (kg R11 equivalent) Photochem Ozone Creation Potential (kg Ethene equivalent) PERFORMANCE ATTRIBUTES Acoustics NRC (Absorption) Static Load (psi)	7.65E-02 7.10E-03 9.87E-09					
Primary Energy (MJ) Global Warming Potential (kg CO ₂ equivalent) Acidification Potential (kg SO ₂ equivalent) Eutrophication Potential (kg PO ₄ ³⁻ equivalent) Ozone Depletion Potential (kg R11 equivalent) Photochem Ozone Creation Potential (kg Ethene equivalent) PERFORMANCE ATTRIBUTES Acoustics NRC (Absorption) Static Load (psi) Light Reflectance	10.47 7.65E-02 7.10E-03					
Acidification Potential (kg SO ₂ equivalent) Eutrophication Potential (kg PO ₄ ³ · equivalent) Ozone Depletion Potential (kg R11 equivalent) Photochem Ozone Creation Potential (kg Ethene equivalent) PERFORMANCE ATTRIBUTES Acoustics NRC (Absorption) Static Load (psi)	7.65E-02 7.10E-03					
Eutrophication Potential (kg PO ₄ ³ equivalent) Ozone Depletion Potential (kg R11 equivalent) Photochem Ozone Creation Potential (kg Ethene equivalent) PERFORMANCE ATTRIBUTES Acoustics NRC (Absorption) Static Load (psi)	7.10E-03					
Ozone Depletion Potential (kg R11 equivalent) Photochem Ozone Creation Potential (kg Ethene equivalen PERFORMANCE ATTRIBUTES Acoustics NRC (Absorption) Static Load (psi)						
Photochem Ozone Creation Potential (kg Ethene equivalen PERFORMANCE ATTRIBUTES Acoustics NRC (Absorption) Static Load (psi)	9.87E-09					
PERFORMANCE ATTRIBUTES Acoustics NRC (Absorption) Static Load (psi)						
Acoustics NRC (Absorption) Static Load (psi)	t) 5.20E-03					
Static Load (psi)						
	0.05					
Light Reflectance	250					
Light Honotanoo	up to 64%					
ASTM F1700	Meets					
Flooring Ingredients: Limestone, Polyvinyl Chloride (PVC), Di(2-ethylhexyl) terephthalate (DEHT), Calcium Phosphate, Magnesium Phosphate						

Inspiring Great Spaces®



Luxury Vinyl (LVT)
Product Declaration

This Product Declaration (1) discloses the known ingredients in their raw material form and (2) provides building industry professionals and other third parties with a summary of environmental and ingredient information about this product. This Product Declaration includes summary life cycle assessment (LCA) information, VOC emissions information, environmental certifications, and key performance attributes for the product.

Declaration Number:	APD-0004									
Declaration Holder:	Armstrong Flooring, Inc.									
Product	Natural Creations® with Diamond 10® Technology, Natural Creations® Classics, Natural Creations® with I-Set™, Parallel® 20, Parallel® 12									
CSI Master Format	09 65 19.23 (Vinyl Tile Flooring)									
Product Website	http://www.armstrong.com/commflooringna/products/lvt									
Product Application	Floor covering choice in commercial spaces: • Hospitality • Education • Healthcare • Assisted Living									
Manufacturing Locations:	Lancaster, PA and/or Wuijang, CN									
Disclosure	All product ingredients known or reported (by a supplier) to be present in a concentration of at least 0.1% (1,000 ppm) or lower concentrations if required by OSHA hazard communications are set forth in the product ingredient table. The CASRN (Chemical Abstract Services Registration Number) is listed for reference. Proprietary ingredients are screened as indicated above, but the name and CASRN are not listed to protect proprietary information. All ingredients are screened against the regulatory and nonregulatory references set forth in the reference section.									
APD Date of Issue:	April 1, 2016									

Sustainability Information

- Certifications for this product:
 - FloorScore® Certification Indoor air quality emissions certification
- Environmental Product Declaration (EPD) Product Specific
 - Certified by ASTM; conforms to the requirements of ISO 14025, 14040, 14044 and ISO 21930
- Extended Producer Responsibility/Recyclable:
 Can be recycled through the Armstrong Flooring Recycling
 Program (www.ArmstrongFlooring.com/reclaim)

Product VOC Emissions

VOC Emissions (Volatile Organic Compounds): Building material is tested and determined compliant in accordance with following VOC emissions standards:

California Department of Public Health (CDPH) V 1.1-2010

▼ Yes □ No □ Not Applicable

Total Volatile Organic Compound (TVOC) Emission Levels:

In accordance with CDPH V1.1-2010





$\overline{\mathbf{X}}$ < 0.5 mg/m ³
\square 0.5-5.0 mg/m ³
$\square > 5.0 \text{ mg/m}^3$

Inspiring Great Spaces®



Luxury Vinyl (LVT) Product Declaration

Product Ingredients

The following table represents the ingredients that are in this product. Each ingredient was screened against the regulatory and non-regulatory references set forth below. When an ingredient is listed on a regulatory or non-regulatory reference, it is noted below with an (X). The results are based on the individual ingredient reviewed in its raw material state, and their inclusion on a reference list does not necessarily pertain to, or represent the form of the ingredient in the final finished product. The following table represents the ingredients that are in this product at concentrations of at least 1,000 ppm (0.1%).

				(X) NOTED IF INGREDIENT IS ON THE LIST								
ROLE	INGREDIENT Listed in descending order based on % by weight.	CASRN	MASS %	IARC1	REACH ²	NTP ³	OSHA⁴	PROP⁵ 65	TRI ⁶ PBT	LIVING ⁷ BUILDING CHALLENGE	GREEN ⁸ SCREEN BM1	NOTES
	Ingredient Name											
Filler	Calcium Carbonate (Limestone)	1317-65-3	60-65%									
Binder	Polyvinyl Chloride (PVC)	9002-86-2 9003-22-9	25-30%							Х		
Plasticizer	Di(2-ethylhexyl) terephthalate (DEHT)	6422-86-2	5-10%									DEHT is a GreenScreen BM3 chemical. BM3 chemicals are recommended for use.
Stabilizer	Calcium Phosphate	10103-46-5	1-2%									
	Zinc Compounds	Proprietary										

References **LEEDv4 Contribution**

The regulatory references include:

IARC – International Agency on the Research of Cancer Terminology Group 1 – Carcinogenic to Humans Group 2 – Probably Carcinogenic to Humans

Group 3 – Possibly Carcinogenic to Humans

Source: http://monographs.iarc.fr/ENG/Classification/index.php

- 2. REACH Registration, Evaluation, Authorization and Restriction of Chemicals Substance of Very High Concern (SVHC) Authorization or Candidate List (as of the date of this declaration) Source: http://echa.europa.eu/addressing-chemicals-of-concern/
- 3. NTP National Toxicology Program Known Human Carcinogen and Reasonably Anticipated Carcinogen **Source:** http://ntp.niehs.nih.gov/?objectid=03C9AF75-E1BF-FF40-DBA9EC0928DF8B15
- 4. OSHA Occupational Safety and Health Administration Carcinogen list Source: https://www.osha.gov/SLTC/carcinogens/index.html
- 5. Prop 65 California Proposition 65 Known to the state of California to cause cancer or reproductive toxicity Source: http://oehha.ca.gov/prop65/prop65_list/Newlist.html
- 6. USEPA TRI Toxic Release Inventory Persisitent, bioaccumulative and toxic (PBT) chemicals Known persistent, bioaccumulative and toxic chemicals and compounds.

Source: http://www.epa.gov/tri/trichemicals/pbt%20chemicals/pbt_chem_list.htm

7. Living Building Challenge™ Red List - was developed by the Cascadia Region Green Building Council and International Living Building

Source: http://living-future.org/living-building-challenge/materials

8. GreenScreen® - is a Chemical Hazard Assessment method developed by the Cleaner Production Action. The Pharos GreenScreen List Translator (LT) was used to screen and identify any Chemical of High Cóncern (LT-1). An LT-1 chemical may be considered equivalent to a Benchmark 1 (BM1) chemical using the full GreenScreen method. **Source:** http://www.cleanproduction.org/Greenscreen.v1-2.php

MRCredit:

Building Disclosure and Optimization -Material Ingredients - Option 1

This Manufacturer Inventory meets the guidelines for this credit.

MRCredit:

Building Disclosure and Optimization -Material Ingredients - Option 2

This product meets the guidelines for International Alternative Compliance Path – REACH Optimization. The end use product and materials do not contain substances that meet REACH criteria for substances of very high concern. The product does not contain ingredients listed on the REACH Authorization or Candidate list.

Printed in United States of America. | © 2017 Armstrong Flooring, Inc. | The Armstrong logo and Armstrong® are trademarks of AWI Licensing LLC. FloorScore® is a registered trademark of the Resilient Floor Covering Institute. | GreenScreen® is a registered trademark of The Tides Center