Modern Farmhouse—White Oak, Clean



Sourced from forests which are carefully managed according to strict Forest Stewardship Council® (FSC®) requirements, this high-grade White Oak offers a more uniform appearance than its reclaimed counterpart. Expect consistent

color tones ranging from cream to tan and a few small knots. This sustainably harvested wood pairs especially well with our custom eco-friendly finishes for floors and paneling.



Pioneer Millworks Modern Farmhouse—White Oak, Clean

CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

09 64 29-Wood strip and plank flooring 06 42 00—Wood Paneling

MANUFACTURER

Pioneer Millworks Pioneer Millworks 1180 Commercial Drive 2609 SE 6th Avenue Farmington, NY 14425 Portland, OR 97202 Phone: 800-951-9663 Phone: 503-719-4800

MATERIALS

- 1. Product Name: Modern Farmhouse White Oak, Clean
- 2. Species/Description: Domestic White Oak, smooth planed
- 3. Source: Sustainably Harvested Forests
- 4. Color: Tones may range from cream to tan. Unlimited color variation is inherent to the product.
- 5. Grade: Clean
- 6. Dimensions:

Solid

TH- 3/4"

WD— 3" to 9" as specified

LG- 18" to 144" random

Engineered

TH- 5/8"

WD-4" to 9" as specified

LG— 12" to 90" random

- 7. Milling: Unfinished: Tongue and Groove Square Edge (TGSQE), Prefinished: Tongue and Groove Micro Bevel Edge (TGMBVE)
- 8. Finish: Unfinished unless specified otherwise
- 9. Hardness: 1260

(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)

10. FSC Claim: (SCS-COC-003998)

Solid: FSC Mix Engineered: FSC Mix

ADDITIONAL INFORMATION

Heartwood: 75% or greater Heartwood

Grain: Clear

Knots: Primarily free of knots. Existing knots generally do not exceed 1/2" diameter.

Texture: Surface is fully planed and clear of saw marks.

Voids: No voids are permitted.

Discoloration: Limited mineral staining is permitted. Checks: Only minor surface checking is permitted.

Substrate: FSC Baltic Birch CPCP grade 9mm thickness for finished 1/2" 12mm thickness for finished 5/8" **CARB2** and **TOSCA** Compliant

Glue: Formaldehyde-free low VOC glue

Moisture Content: Kiln dried 6-9% prior to milling.

LEED INFORMATION

MRc3: N.A. MRc4: N.A

MRc5: Regional Materials (call for details)

MRc7: Certified Wood: FSC Mix

RECOMMENDED OVERAGE

Recommend 7-12% additional material for on-site grading, trimming and installation factors.























Information is deemed reliable but subject to change, All photos for representation only. Additional information available at our website or call our wood design experts.