



USG LEVELROCK® BRAND

WOOD PRIMER

High-quality floor underlayment primer

- Enhances bond between subfloor and underlayment
- Low odor
- Fast-drying
- Resists mold

DESCRIPTION

USG Levelrock® Brand Wood Primers (Concentrate and Powdered) are designed and manufactured by USG to improve adhesion to wood subfloors including OSB and plywood. The surfaces of these floors must be sound and non-friable. For old and new concrete floors and existing floor coverings such as vinyl tile, ceramic tile, linoleum and varnished wood floors, use USG Levelrock™ Acrylic Concrete Primer.

These low odor primers are sprayed, broomed on or paint roller-applied to the subfloor by USG Levelrock applicators prior to installing USG Levelrock® engineered cementitious underlayments in all types of commercial and residential flooring applications. Available in concentrate and powdered form (which require diluting with water), the primers are fast drying and resist mold.

LIMITATIONS

1. Do not use in exterior applications.
2. Do not apply at temperatures below 45 °F (7 °C) or above 120 °F (49 °C).
3. Do not apply on excessively dusty or dirty subfloors.

VOC EMISSIONS

USG Levelrock® Wood Primers achieved GREENGUARD Gold Certification and qualify as a "Low Emitting" material per California Department of Public Health CDPH/EHLB/ Standard Method (CA Section 01350) for school classroom and private office modeling scenarios, and meets USGBC's LEED® v4 emission requirements.



EXTENDED WARRANTY

An extended warranty may apply when using USG Levelrock Wood Primer in a system application. Please contact USG for further details.

APPLICATION

Read and follow all cautions and warnings on USG Levelrock Wood Primer product labels. Refer to each product's Safety Data Sheet (SDS) for additional information. Floor to be primed must be sound, clean, free of alkali and dry. Remove dirt, wax, polish, paint and all foreign material that would interfere with a good bond.

Minimum dry time for primer application is 1 hour. Dry times up to 3 hours will greatly enhance bond strength of underlayment to subfloor. A minimum building temperature of 45 °F (7 °C) must be maintained for all USG Levelrock Wood Primers during the drying period. Cooler temperatures and high humidity will prolong dry times.

For further details on application requirements and the most up-to-date product information, please see usgperformanceflooring.com.

STORAGE

Protect from freezing, and do not store above 120 °F (49 °C). USG Levelrock Wood Primer (concentrate) has limited freeze thaw protection. If accidentally frozen, allow to thaw at room temperature. Stir to a homogenous state before using. Do not use material that is coagulated or has excessive settlement that cannot be readily remixed. Discard questionable material. Do not over-stir or use a high-speed mixer, as excessive air entrainment may result.

USG Levelrock Wood Primer (powdered), in dry form, is not affected by freezing temperatures, but should be stored in a dry area. In mixed form, it may be stored for up to 2 weeks, but must be remixed prior to use, as some settlement will occur. Do not use material that has excessive settlement that cannot be readily remixed.

SUBMITTAL APPROVALS

Job Name	
Contractor	Date

PRODUCT INFORMATION

See usgperformanceflooring.com for the most up-to-date product information.

GREENGUARD INFORMATION

GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg.

CAUTION

Dust from mixing may cause irritation to eyes, skin, nose, throat and upper respiratory tract. Use only in a well-ventilated area, wear a NIOSH/MSHA-approved respirator. Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. If on skin: Wash with plenty of water. If swallowed or irritation persists, call physician. Keep containers closed when not in use. For more information call Product Safety: 800-507-8899 or see the SDS at usg.com.

KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks USG, LEVELROCK, IT'S YOUR WORLD, BUILD IT., the USG logo, the design elements and colors and related marks are trademarks of USG Corporation or its affiliates. LEED is a registered trademark of U.S. Green Building Council.

NOTE

The information in this document is subject to change without notice. USG Corp. and/or its affiliates assumes no responsibility for any errors that may inadvertently appear in this document. Consult your USG sales office or representative for information.

NOTICE

We shall not be liable for consequential, incidental or special damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to the replacement of defective goods or a refund of the purchase price, at USG's option, and does not include costs of labor, floor-covering materials, or any other costs associated with material replacement. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read applicable SDSs and literature before specification and installation.

800 USG.4YOU
800 (874.4968)
usgperformanceflooring.com
usg.com

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

IG1505-USA-ENG/rev. 9-19
© 2019 USG Corporation and/or
its affiliates. All rights reserved.
Printed in U.S.A.

