NOTE: Not all dimming ballast models are compatible with all fixture styles. See specification sheets or consult factory for details.			Т8			T5		Long Twin Tube
						T5S	T5H0	
Manufacturer	Description	Catalog #	17	25	32	28	54	40TT
Advance Mark X Line Voltage	1-lamp	EBD1*AD*MKX	~	~	V	V	V	/
	2-lamp	EBD2*AD*MKX	~	/	/	V	V	V
	3-lamp	EBD3*AD*MKX	_	_	V			_
Advance Mark VII Low Voltage	1-lamp	EBD1*AD*MK7	~	V	V	V	V	V
	2-lamp	EBD2*AD*MK7	V	V	V	V	V	V
	3-lamp	EBD3*AD*MK7	~	V	V	_	_	_
	4-lamp	EBD4*AD*MK7	_	V	V	_	_	_
Lutron EcoSystem® H-Series 1% Dimming Digital Control ¹	1-lamp	EBD1*LU*EHD¹	_	_	V	1 2	1 2	_
	2-lamp	EBD2*LU*EHD1	_	_	V	1 2	1 2	_
	3-lamp	EBD3*LU*EHD1	_	_	_	_	_	_
Lutron Hi-lume® 3D 1% Dimming 3-Wire, Digital	1-lamp	EBD1*LU*HILUME 3D	~	V	V	V	V	V
	2-lamp	EBD2*LU*HILUME 3D	~	V	V	V	V	V
	3-lamp	EBD3*LU*HILUME 3D	~	_	V	_	_	V
Lutron EcoSystem®3	1-lamp	EBD1*LU*EC53	~	V	V	V	V	V
	2-lamp	EBD2*LU*EC53	~	V	V	V	V	V
	3-lamp	EBD3*LU*EC53	~	_	V	_	_	_
Lutron EcoSystem® Reduced Wattage (25W, 28W, 30W), 10% Dimming, Digital Control, 3-Wire Control³	1-lamp	EBD1*LU*EC5RW3	_	_	V	_	_	_
	2-lamp	EBD2*LU*EC5RW3	_	_	V	_	_	_
	3-lamp	EBD3*LU*EC5RW³	_	_	V	_	_	_
			Step-Dimm	ing Ballasts				
Switchable 50% step-dimming ballast	2-lamp	EBSD2*S50		_	V		_	
Step-dimming, .95 ballast factor	2-lamp	EBSD(95)2	_	_	_	~	_	_
Step-dimming 1.15 ballast factor	2-lamp	EBSD(115)2	_	_	_	~	_	_
Step-dimming .80 ballast factor	2-lamp	EBSD(80)2	_	_	_	_	V	_

System cable and modules furnished by others if required.
Available with 4' lamps only.
System cable furnished by others if required.