



Contour Series Wood Stone

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Tarkett Contour Series Wood Stone Luxury vinyl floor covering with Techtonic™ protection to deliver unmatched durability in high-traffic areas in a plank design.

1.2. Suitable for commercial working environments and offices:

- Education – Classrooms, corridors, multipurpose rooms, laboratories, cafeterias, lavatories
- Offices – Break rooms, offices, corridors, cafeterias, lavatories
- Retail – Sales areas, offices
- Healthcare – Exam rooms, lobbies, corridors
- Hospitality – Corridors, vending areas, lobbies

1.3. Manufacturer:

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com

1.4. Proprietary Product Description:

1.3.1. **Construction:** Tarkett Contour is constructed on a unique composite structure built with homogeneous polymeric calendared layers with a 32 mil wear layer and state-of-the-art Techtonic™ protective finish for long term performance. Tarkett's Techtonic™ is a massive shift forward in performance for hard surface floors. Its advanced polyurethane technology is super tough, resisting scratching, abrasions, scuffing and staining.

1.3.2. Styles:

Contour Series Wood Stone

- **Finish:** Techtonic™
- **Wear layer Thickness:** 32 mil (0.8 mm)
- **Edge treatment:** Square Edge (SE)
- **Overall thickness:** .120" (3 mm)
- 50 Wood / 27 Stone patterns

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Meets ASTM F 1700, Class III, Type B performance
- 2.2. **Static Load Limit** (ASTM F970): 250 psi, $\leq 0.005''$
- 2.3. **Residual Indentation** (ASTM F1914): Passes
- 2.4. **Static coefficient of friction** (ASTM D 2047): ≥ 0.5 SCOF
- 2.5. **Dimensional Stability** (ASTM F2199): Passes
- 2.6. **Resistance to Heat** (ASTM F1514): $\Delta S \leq 8.0$

2.7. **Resistance to Light** (ASTM F1515): $\Delta S \leq 8.0$

2.8. **Chemical Resistance** (ASTM F925): Passes

2.9. **Fire Performance, Critical Radiant Flux** (ASTM E648): Class 1 ($> 0.45 \text{ W/cm}^2$)

2.10. **Smoke Density** (ASTM E648): ≤ 450

3. INSTALLATION

See Contour Luxury Vinyl Plank installation instructions for complete details.

3.1 Adhesives:

- **Tarkett RollSmart Adhesive:**
Coverage: 350 – 400 sq. per gallon
(3/8" Nap Paint Roller used with a paint tray)
- **Tarkett 959 Adhesive:**
Coverage:
Porous Substrate: 150-175 sq. ft. per gallon
Non-porous Substrate: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Polyurethane Adhesive:**
Coverage:
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 25 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Contour Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



Contour Series Wood Stone

Product Specification

EMBOSS OPTIONS

	Frost (FR)	Natural Grain (NG)	Quarry (QU)	Rough (RG)	Sawn (SW)	Tick (TK)
Antique Wood (PCAN)						
0383	•	S			•	•
3815, 3816	•		S			•
0351, 0353, 0357, 0359, 3512		•		S	•	•
0301, 0302, 0305, 0306, 3720		•		•	S	•
3810, 3811, 3812		•		•	S	•
Exotic Wood (PCEX)						
3205		S		•		•
3314		•		S		•
3210, 3213, 3214, 3302, 3310, 3311, 3312, 3324, 3625, 3901, 3301	•	•		•		S
Grand Ash (PCGA)						
3632, 3634, 3635		•		S		•
Modern Wood (PCMD)						
0361, 3306	•	S		•		•
3820, 3821, 3822	•		•	S		•
3823, 3824, 3825				S	•	
3602, 3604, 3606, 3610, 3732, 3104		•		•		S
NuGrain (PCNU)						
3710, 3712, 3715, 3717		•	•	•		S

	Fresco (FC)	Frost (FR)	Pathway (PH)	Quarry (QU)
Concrete (PCCN)				
0710, 0712, 0718	•		•	S
7241, 7243	•	•	S	•
Fossil Stone (PCFS)				
0830, 0834	•	•	•	S
Legacy Stone (PCLE)				
0553, 0557	•	•	S	•
0541		•	•	S
Modern Stone (PCMS)				
0604, 0606, 0610, 0612, 0614, 0616, 0620, 0624, 0630, 0631, 0632, 0633	•		•	S
Passageway (PCPA)				
0840, 0841, 0842			S	•
Vestige (PCVE)				
1018, 1019		•		S

S = Standard

Appropriate surface texture, pattern, and color play a significant role in LVT performance, wear and maintenance requirements. Please consult your account executive to determine the emboss that will best fit the design and performance goals for your project.

SIZES

	12x24	18x18	36x36
Contour® Series Stone			
Concrete (PCCN)	•	•	•
Fossil Stone (PCFS)	•	•	
Legacy Stone (PCLE)	•	•	
Modern Stone (PCMS)	•	•	
Passageway (PCPA)	•	•	
Vestige (PCVE)	•	•	
	4x36	6x36	6x48
Contour® Series Wood			
Antique Wood (PCAN)	•	•	•
Exotic Wood (PCEX)	•	•	•
Grand Ash (PCGA)	•	•	•
Modern Wood (PCMD)	•	•	•
NuGrain (PCNU)	•	•	•

Tarkett North America

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139

800.899.8916

info@tarkettna.com

www.tarkettna.com