



Applause III #02803

Product Specification

Face Construction	Imperial	Metric
Construction	Level Loop	
Face Weight	18 oz/sq yd	610.2 g/sq m
Gauge	1/13	50.4 rows/10 cm
Stitches per Inch	8.2	32.3 pu/10 cm
Tuft Density	104.96 tufts/sq in	16.3 tufts/sq cm
Pile Height Average	0.117 inch	3.0 mm
Pile Thickness	0.087 inch	2.2 mm
Density Factor	7,448 oz/cu yd	275.6 kg/cu m
Fiber System	Dynex SD® / Dynex® Nylon	
Dye Method	50% Solution Dyed / 50% Yarn Dyed	
Fluorine-Free Soil Protection	Eco-Ensure	9.4 Kilotex
Primary Tufting Substrate	Synthetic Non-Woven	
Pattern Match	Not Required	

Third Party Environmental Certifications

Product		Recycled Content*		NSF 140	Cradle to Cradle
		Overall	Postconsumer	SCS Certified	Certified™ v3.1**
Certified	ER3® Modular	45-66%	14%	Gold	
Certified	ethos® Modular with Omnicoat Technology™	47-75%	28%	Platinum	Silver
Certified	Powerbond® Cushion	7-33%	7%	Gold	
Certified	Flex-Aire Modular® Cushion	21-41%	4%	Gold	
Certified	Powerbond® Medfloor®	7-33%	7%		

*Minimum recycled content certified by Scientific Certification Systems (SCS) and varies by product style.

**Cradle to Cradle Certified is a certification mark licensed by the Cradle to Cradle Products Innovation Institute

Product Testing/Information

Antimicrobial Chemicals	No antimicrobials (EPA Registered pesticides) added to product (ASTM E2471-05)
Electrostatic Propensity	2.2 kV (AATCC 134); Permanent Conductive Fiber
Surface Flammability	Passes CPSC FF 1-70 (ASTM D-2859)
Flooring Radiant Panel	Class 1 (mean average CRF: 0.45 w/sq cm or higher) (ASTM E-648)
Smoke Generation	Less than 450 (ASTM E-662)
Colorfastness to Light	≥ 4 after 60 hours (AATCC 16E)
Soil Protection	Application Rate: 2% of Face Weight

Installation Methods

Peel and Stick	RS Adhesive System - Full Coverage Peel & Stick
Wet Spread	Backing specific Tandus Adhesives
Installation Method	Monolithic

Product Notes

- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice. Colors may vary slightly from dye lot to dye lot.
- U.S. Patent numbers: 4,849,297; 4,849,267; 5,728,741; 5,855,981; 5,914,353; 6,406,574
- The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.

Tarkett North America

Technical Services Department
1000 Vista Drive
Dalton, GA 30721
800.248.2878 Fax 706.259.2136
info@tarkettna.com

www.tarkettna.com

© 2019 Tarkett USA Inc. 01/2019



Modular Options

IMPERIAL	METRIC	TEST METHOD
----------	--------	-------------

Warranty: Lifetime limited warranty against excessive surface wear, static, delamination, edge ravel, zippering & backing resiliency loss.

ER3® Modular

Total Minimum Recycled Content	53.6%					SCS Certified total 45-66%
Pre-Consumer	36.9%					SCS Certified
Postconsumer	16.7%					SCS Certified
Third Party Certification NSF-140	Gold					SCS Certified
Product Size	24" x 24" Tile					
Secondary Backing	100% Recycled Content with Tru Bloc (Barrier System)					
Intermediate Layer	Fiberglass Reinforced Sealant					
Product Construction	No Delamination per ASTM D-3936					
Secondary Backing Density	65	lbs/cu ft		1041	kg/cu m	
Secondary Backing Thickness	0.087	inch		2.2	mm	
Total Weight with RS / Non-RS	128.5	126.9	oz/sq yd +/-5%	4358	4303	g/sq m
CRI Green Label Plus Certification	GLP1366					

ethos® Modular with Omnicoat Technology™

Total Minimum Recycled Content	58.1%					SCS Certified total 47-75%
Pre-Consumer	23.6%					SCS Certified
Postconsumer	34.5%					SCS Certified
Third Party Certification NSF-140	Platinum					SCS Certified
Cradle to Cradle Certification	Silver (Certification #1904)					Cradle to Cradle Certified™ v3.1
Product Size	24" x 24" Tile					
Secondary Backing	50% Recycled Content					
Intermediate Layer	Fiberglass Reinforced Sealant					
Product Construction	No Delamination per ASTM D-3936					
Secondary Backing Density	65.0	lbs/cu ft		1041	kg/cu m	
Secondary Backing Thickness	0.050	inch		1.3	mm	
Total Weight	95.9		oz/sq yd +/-5%	3250.7	g/sq m	
CRI Green Label Plus Certification	GLP8320					



Flex-Aire Modular® Cushion

Total Minimum Recycled Content	25.2%					SCS Certified total 21-41%
Pre-Consumer	19.5%					SCS Certified
Postconsumer	5.7%					SCS Certified
Third Party Certification NSF-140	Gold					SCS Certified
Product Size	24" x 24" Tile					
Secondary Backing	Fiberglass Reinforced Composite Closed Cell Cushion					
Intermediate Layer	Fiberglass Reinforced Sealant					
Product Construction	No Delamination per ASTM D-3936					
Cushion Weight	35.5	oz/sq yd		1203	g/sq m	ASTM D-3574
Cushion Density	18.5	lbs/cu ft		296	kg/cu m	ASTM D-3574
Cushion Thickness	0.156	inch		4.0	mm	ASTM D-3574
Total Weight with RS / Non-RS	117.1	115.7	oz/sq yd +/-5%	3971	3924	g/sq m
Compression Set	Max. 10%					ASTM D-3574
Compression Deflection	5 Min. 25 max lbs/sq inch @ 25%	352		1758	g/sq cm	ASTM D-3574
CRI Green Label Plus Certification	GLP6558					



Powerbond® Options

IMPERIAL	METRIC	TEST METHOD
----------	--------	-------------

Warranty: Lifetime limited warranty against excessive surface wear, static, delamination, edge ravel, zippering & backing resiliency loss.

Powerbond Cushion

Total Minimum Recycled Content	8.5%				SCS Certified total 7-33%
Pre-Consumer	0.0%				SCS Certified
Postconsumer	8.5%				SCS Certified
Third Party Certification NSF-140	Gold				SCS Certified
Product Size	6 ft.	1.8	m		
Cushion	Closed Cell Cushion				
Heterogeneous Construction	No Delamination per ASTM D-3936				
Cushion Weight	35.5 oz/sq yd	1203	g/sq m		ASTM D-3574
Cushion Density	18.5 lbs/cu ft	296	kg/cu m		ASTM D-3574
Cushion Thickness	0.156 inch	4.0	mm		ASTM D-3574
Total Weight with RS / Non-RS	79.0 76.7 oz/sq yd +/-5% 2679	2601	g/sq m		
Compression Set	Max. 10%				ASTM D-3574
Compression Deflection	7 Min. 25 max lbs/sq inch @ 25% 492	1758	g/sq cm		ASTM D-3574
CRI Green Label Plus Certification	GLP9744				

Powerbond Medfloor®

Total Minimum Recycled Content	9.0%				SCS Certified total 7-33%
Pre-Consumer	0.0%				SCS Certified
Postconsumer	9.0%				SCS Certified
Product Size	6 ft.	1.8	m		
Cushion	Medfloor				
Heterogeneous Construction	No Delamination per ASTM D-3936				
Cushion Weight	37 oz/sq yd	1254	g/sq m		ASTM D-3574
Cushion Density	36 lbs/cu ft	577	kg/cu m		ASTM D-3574
Cushion Thickness	0.085 inch	2.2	mm		ASTM D-3574
Total Weight	78.2 oz/sq yd +/-5%	2652	g/sq m		
Compression Set	Max. 10%				ASTM D-3574
Compression Deflection	29 lbs/sq inch @ 25%	2039	g/sq cm		ASTM D-3574
CRI Green Label Plus Certification	GLP9744				