



959 Vinyl Tile and Plank Adhesive

Product Specification

1. PROPRIETARY PRODUCT

- 1.1. Product Description:** Tarkett 959 adhesive is a solvent- free easy to apply adhesive specifically formulated for installing Access, Aloft Glue Down, Azterra, Color Essence, Color Essence SR, Cortina, Grande SR, Crossroads, FiberFloor, Gemstone, ID Freedom, ID Inspiration, Maintstreet Carpet Tile, Contour LVT, Event LVT, Venue LVT, Collections Infinies/Riot/Alphabet LVT, Indigenous Earth LVT, and More Than Wood LVT, Origins, Performa, PermaStone, SureStart Underlayment, TruTex, Vinyl Sheet (Felt) and Vista.

1.2 Manufacturer:

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkettna.com
E-mail: info@tarkett.com

1.3 Physical Characteristics:

- Base – Acrylic
- Color – White
- Shelf Life – 2 year in unused, properly stored container
- Freeze thaw - Protect from freezing, do not freeze
- Working Time – Up to 2 hours
- Contains no hazardous or carcinogenic ingredients as defined by OSHA chemicals and meets all federal, state and local air quality regulations.
- SCAQMD Rule 1168 – VOC compliant (0 g/L calculated)

1.4 Adhesive Coverage:

All Flooring types listed above.

Porous: 1/16" x 1/16" x 1/16" V – notch
trowel not to exceed 150 – 175 sq. ft. per gallon

Non-Porous: 1/16" x 1/32" x 1/32" U – notch
trowel not to exceed 250 – 300 sq. ft. per gallon

2. SUBSTRATE PREPARATION

NOTE: A clean substrate is essential! Suitable substrates include on, below, or above grade concrete

(Within moisture and alkalinity specifications) and APA underlayment grade plywood. All substrates must be clean, structurally sound, smooth, dry and free of waxes, existing adhesives, dirt, dust, grease, oil and paint, curing compounds or sealers. This adhesive cannot be used over chemically cleaned substrates. All concrete substrates, preparation and testing procedures must conform to appropriate ASTM F710 guidelines. Tarkett 959 Vinyl Tile and Plank adhesive may be used for installations over concrete substrates with up to 90% RH per latest version of ASTM F2170 and 8lbs per 1000 sf/24hrs per the latest version of ASTM F1869 and pH between 7.0 – 10.0. The interior air temperature and Relative Humidity must be maintained between 65 - 85°F and 40-60% RH, and the substrate temperature should be at least 5 degrees F. higher than the Dew Point.

Manual: Refer to container label for complete installation details.

3. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

4. Traffic:

All traffic must be restricted for a minimum of 24 hours after installation. Restrict heavy traffic, rolling loads, or furniture placement for 72 hours after installation.

Wait at least 48 hours before beginning initial maintenance.

5. LIMITED WARRANTY

Adhesive warranty is a system warranty covered under the product that is recommended to be installed in conjunction with this adhesive. Refer to Tarkett limited warranty.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916 Ext. 9297 Fax 440.632.5643
info@tarkettna.com

www.tarkettna.com