



## Vent Cove Wall Base

## Product Specification

### 1. PROPRIETARY PRODUCT/MANUFACTURER

#### 1.1. **Proprietary Product:** Resilient Vent Cove Wall Base

#### 1.2. **Manufacturer:**

Tarkett North America      Phone: (800) 899-8916  
30000 Aurora Rd.      (440) 543-8916  
Solon, Ohio 44139  
Web: [www.tarkettna.com](http://www.tarkettna.com)

#### 1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Vent Cove Wall Base is manufactured from a homogeneous composition of 100% synthetic rubber, high quality additives, and colorants designed specifically to meet the performance requirements of ASTM F-1861, Type TS, Group 1 (solid) Standard Specification for Resilient Wall Base. Vent Cove Wall Base is designed for hardwood floating floor constructions and is equipped with vertical, semi-circular vents along the back side of the wall base to ensure proper air circulation under the floor and permits free expansion of the floor.

#### 1.3.2. **Styles/ Physical Characteristics:**

- **Product code:** VCO-XX
- **Outside corners:** VCOC-XX with 3-5/8" (14.3 cm) returns and 0.9 lbs./piece
- **Size:** 4" (10.16 cm) high by 0.260" (6.60 mm) thick coved profile with a 3" (7.62 cm) long by 0.300" (7.62 mm) thick toe. Back surface grooved with vertical semi-circular vents (15 vents per 4 ft. length)
- **Weight:** 4.6 lbs. per length
- **Length:** 4' (1.22 m) Packaging: 10 lengths per carton

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Hardness:** ASTM D 2240 – Not less than 85 Shore A
- 2.2. **Fire Resistance:** Meets ASTM E84 (Flame spread & smoke) – Class B, ≤ 450
- 2.3. Meets or exceeds the performance requirements for resistance to heat/light aging, chemicals, and dimensional stability when tested to the methods as described in ASTM F-1861.

### 3. INSTALLATION

See vent cove wall base installation instructions for complete details.

#### 3.1. **Adhesives:**

- **Tarkett 960 Adhesive:**  
Coverage:  
Porous Substrate: 200-250 linear ft. per gallon
- **Tarkett 946 Premium Contact Adhesive:**  
Coverage:  
Non-porous Substrate:  
1 Quart (0.95 liters) – 24 to 36 sq. ft.  
1 Gallon (3.79 liters) – 100 to 150 sq. ft.

### 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

### 5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

### 6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Vent Cove Installation and Maintenance Instructions for complete maintenance details.

### 7. TECHNICAL SERVICES

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at 1-800-899-8916.

#### **Tarkett North America**

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkettna.com](http://www.tarkettna.com)