

Silvius Collection



DESIGN

Product Type:	Commercial Hardwood
Overall Thickness:	9/16"
Finish:	Aluminum Oxide
Species:	White Oak
Size:	7" W x 18" to 72" L (Random lengths)
Square Feet Per Carton:	22.5 sf/ctn
Pounds Per Carton:	55 lbs/ctn
Trim And Moldings:	Color coordinated pre-finished trims and moldings: reducer strip, baby threshold, t-molding, flush stair nosing and quarter round
Installation Method:	Glue, nail, staple, or float
Recommended Adhesive:	M92X Modified Moisture-Cured Urethane Adhesive, M1000 UltraTack™ Advanced 3 in 1 Adhesive for enhanced acoustics and high moisture slabs
Underlayment:	SilentGuard Underlayment for use only when floating engineered hardwood
Grade Level:	All

SUSTAINABILITY

Certification:	FloorScore® certified
CARB II Compliant:	Yes
Lacey Act Compliant:	Yes

PERFORMANCE

Construction:	Engineered Commercial Hardwood
Resistance To Chemicals:	ASTM F925- Passes
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm ² , Class 1
Smoke Density:	ASTM E662 Part A - Less than 450
Electro Static Propensity:	AATCC 134 - Passes - = 3.5 KV (Step Only)

SERVICE

Warranties:	Limited 5 Year Light Commercial
-------------	---------------------------------



22
Fern



24
Bark



25
Fawn



26
Sedona



27
Sand



28
Fossil



30
Pebble



80
Earth